WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction | | Section number | | Township number | Range number | |
|--|--------------|------------------|-----|----------------|--|--|---|--------------|
| 1. Location of well: | Haskell | NW 1/4 NW 1/4 SW | 1/4 | 19 | | т 29 s | r 31W | E/W |
| 56 from Jct. 56 & 83 at Sublette. North R.R. or s | | | | | | | | |
| City, state, zip code: | | | | | | ublette, Kansas 67877 6. Bore hole dia 9=7/8 in. Completion dat 10=12=78 | | |
| 4. Locate with "X" in section below: N | | | | | | 6. Bore hole dia 9=778 in. Well depth 360 ft. | Completion date U | -12=/10 |
| SW4, Sec. 19, T29S, R31W, Haske Kansas. | | | | ell Co., | | 7 Cable toolXRotary Driven Dug Hollow rod Jetted Bored Reverse rotary 8. Use: X Domestic Public supply Industry Irrigation Air conditioning Stock Lawn Oil field water Other | | |
| sw sE s | | | | | 9. Casing: Material Height: Above or below Threaded Surface 12 in. RMP PVC Weight lbs./ft. | | | |
| 1 Mile | | | | | | Dia.5in. t310_ft. dep | th!Wall Thickness:_inc | hes or |
| 5. Type and color of material | | | | From | То | Diain. to ft. depth gage No. <u>250</u> 10. Screen: Manufacturer's name Peerless | | |
| top soil | | | | 0 | 4 | Plastics | | |
| tan sandy clay | | | | 4 | 62 | Slot/gauze1/8" Set between 310 | | |
| fine sand | | | | 62 | 84 | ft. andft. Gravel pack? X_ Size range of material 2.8mm 11. Static water level:mo./day/yr. 213ft. below land surface Date 9/11/78 12. Pumping level below land surfaces:NO Testft. after hrs. pumping g.p.mft. after hrs. pumping g.p.m. Estimated maximum yield g.p.m. 13. Water sample submitted: mo./day/yr Yes X_ No Date 14. Well head completion: X_ Pitless adapter Inches above grade 15. Well grouted? Yes With: Neat cement Bentonite Concrete Depth: From ft. to 20 ft. 16. Nearest source of possible contamination: Type Unknown | | |
| fine sand, clay streaks | | | | 84 | 94 | | | |
| fine to medium sand, clay streaks | | | | 94 | 118 | | | |
| fine to medium sand, small gravel | | | | 118 | 202 | | | |
| fine to medium sand, clay streaks | | | | 202 | 212 | | | |
| fine to medium sand, few clay streaks | | | | 212 | 298 | | | |
| tan sandy clay, fine sand streaks | | | | 298 | 312 | | | |
| fine to medium sand, small gravel streaks, | | | | 312 | 386 | | | |
| few clay streaks fine sand, clay streaks | | | | 386 | 398 | | | |
| fine sand | | | | 398 | 422 | Well disinfected upon comple | etion? X Yes | — <u>№</u> k |
| tan clay, fine sand streaks | | | | 422 | 444 | 17. Pump: Manufacturer's name | X Not installed | " _ |
| tan clay | | | | 444 | 480 | Model number | | |
| | | | | | | Type: Submersible | Turbine | 1 1 |
| (Use a second sheet if needed) | | | | | | Jet Centrifugal | Recipro | cating |
| 18. Elevation: Topography: Hill Slope XX Upland Valley | 19. Remarks: | | | | | 20. Water well contractor's and the second s | y jurisdiction and this viedge and belief. Co. Inc. 1 686 Garden | report |