

1 LOCATION OF WATER WELL		Fraction of N line of E line		Section Number		Township Number		Range Number	
County: Haskell		650S $\frac{1}{4}$ 1980W $\frac{1}{4}$ NE $\frac{1}{4}$		25		T 29 S		R 31W E/W	
Distance and direction from nearest town or city? 2 W, 2 S of Copeland, Kansas				Street address of well if located within city?					
2 WATER WELL OWNER:		Gabbert & Jones, Inc.							
RR#, St. Address, Box # :		830 Sutton Pl.							
City, State, ZIP Code :		Wichita, Kansas 67202							
		Board of Agriculture, Division of Water Resources Application Number: Unknown							
3 DEPTH OF COMPLETED WELL		307 ft. Bore Hole Diameter 8 in. to 307 ft., and in. to ft.							
Well Water to be used as:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 <u>Oil field water supply</u> 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well							
Well's static water level 210 ft. below land surface measured on 11 month 28 day 1980 year									
Pump Test Data		Well water was ft. after hours pumping gpm							
Est. Yield 60 gpm: Well water was ft. after hours pumping gpm									
4 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile Casing Joints: <u>Glued</u> Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 <u>PVC</u> 4 ABS 7 Fiberglass Threaded							
Blank casing dia 5 in. to 287 ft., Dia 12 in. to 2.8 in. to Sch. 40 ft.									
Casing height above land surface 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 <u>PVC</u> 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)							
Screen or Perforation Openings Are:		5 Gauzed wrapped 8 <u>Saw cut</u> 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
Screen-Perforation Dia 5 in. to 287 ft., Dia 307 in. to ft.									
Screen-Perforated Intervals: From 287 ft. to 307 ft., From ft. to ft.									
Gravel Pack Intervals: From 10 ft. to 307 ft., From ft. to ft.									
5 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 <u>Bentonite</u> 4 Other Grouted Intervals: From 0 ft. to 10 ft., From ft. to ft.							
What is the nearest source of possible contamination:		10 Fuel storage 14 Abandoned water well 1 Septic tank 4 Cess pool 7 Sewage lagoon 11 Fertilizer storage 15 <u>Oil well/Gas well</u> 2 Sewer lines 5 Seepage pit 8 Feed yard 12 Insecticide storage 16 Other (specify below) 3 Lateral lines 6 Pit privy 9 Livestock pens 13 Watertight sewer lines							
Direction from well South How many feet 60 ? Water Well Disinfected? Yes No									
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, date sample was submitted month day year Pump Installed? Yes No									
If Yes: Pump Manufacturer's name Model No. HP Volts									
Depth of Pump Intake ft. Pumps Capacity rated at gal./min.									
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other									
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 11 month 28 day 1980 year									
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186									
This Water Well Record was completed on 12 month 15 day 1980 year under the business name of Kellys Water Well Service by (signature) <i>Kelly Price</i>									
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG					
		0 65 Clay							
		65 140 Gravel							
		140 270 Clay							
		270 307 Gravel							
ELEVATION: Unknown									
Depth(s) Groundwater Encountered 210 ft. 2 ft. 3 ft. 4 ft.		(Use a second sheet if needed)							

OFFICE USE ONLY

T

829

R

31

EWD

SEC.

825

SE 1/4

NW 1/4

NE 1/4