

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Haskell</u>	<u>SW</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$	<u>19</u>	<u>T 29S S</u>	<u>R 31 E</u> <b>(W)</b>

Distance and direction from nearest town or city street address of well if located within city?

Sublette: 83/56 Jct. 6 NE on 56 to RD SS--6/10 N and E into--

2 WATER WELL OWNER:	<u>Shawn Stapleton</u>
RR#, St. Address, Box # :	<u>HC 1, Box 69B</u>
City, State, ZIP Code :	<u>Sublette, KS 67877</u>

Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>440</u> ft. ELEVATION:
--	---

Depth(s) Groundwater Encountered 1 292 ft. 2 325 ft. 3 09-12-05 ft.

WELL'S STATIC WATER LEVEL 292 ft. below land surface measured on 09-12-05 mo/day/yr

Pump test data: Well water was 55 gpm. Well water was 55 ft. after 1 hours pumping 55 gpm

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Domestic (lawn & garden)
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No **X**; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes **X** No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter <u>5</u> in. to <u>420</u> ft. Dia			Threaded
Casing height above land surface <u>+2</u> in., weight <u>3.706</u> lbs./ft. Wall thickness or gauge No. <u>SDR 21</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized Steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Guazed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
		7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:			11 None (open hole)
GRAVEL PACK INTERVALS:			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other <u>Hole Plug</u>
GROUT INTERVALS:	From <u>1</u> ft. to <u>25</u> ft.	From <u>25</u> ft. to <u>440</u> ft.	From <u>440</u> ft. to <u>440</u> ft.	From <u>440</u> ft. to <u>440</u> ft.
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface	395	430	Sand
2	18	Sandy Clay	430	440	Sandy Clay
18	36	Clay			
36	81	Sandy Clay			
81	112	Clay			
112	123	Sand			
123	146	Sand and Gravel			
146	194	Sand			
194	246	Sand--hard			
246	290	Sand--medium hardness			
290	352	Sand--loose			
352	370	Sand and Clay streaks			
370	390	Sandstone			
390	395	Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09-12-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No KWCL 430 This Water Well Record was completed on (mo/day/yr) 09-12-05 under the business name of Howard Drilling Co. Box 806 Beaver, OK 73932 by (signature) Howard Drilling Co.