WATER WELL RI	ECORD	Form W	WC-5	Division of Wate	r Resources App. No	6,218 & 12,565	
1 LOCATION OF W	ATER WELL:	Fraction		Section Number	Township No.	Range Number	
County: HASKELL		1/4 SW 1/4 NW		34	T 29 S	R 31 □E 🗗 W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here				Global Positioning System (GPS) information: Latitude:37.47848			
SE CORNER OF SUBLETTE - 8 MILES EAST, 1,465 FT. NORTH				Longitude: 100.70663 (in decimal degrees)			
& 5,175 FT. WEST				Elevation:			
2 WATER WELL OWNER: BRYANT LAND & CATTLE, INC.				Datum: WGS 84, NAD 83, NAD 27 Collection Method:			
RR#, Street Address, Box #: PO BOX 87				T GPS unit (Make/Model: CarminST62)			
City, State, ZIP Code : COPELAND, KANSAS 67837				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m							
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL							
SECTION BOX: Depth(s) Groundwater Encountered (1)							
N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr							
EST. YIELDgpm. Well water was							
w E Bore Hole Diameter .39in. toft., andin. toft.							
WELL WATER TO BE USED AS:							
SW - SE -							
Was a chemical/bacteriological sample submitted to Department? Yes No							
S If yes, mo/day/yr sample was submitted							
water well distinceted: Tes 12 No							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 16							
Casing height above land surface							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
✓ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify) ☐ Brass ☐ Galvanized Steel ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From							
From							
GRAVEL PA	CK INTERVALS:						
From							
Grout Intervals: From							
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)							
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well N/A							
FROM TO	LITHOLOG	GIC LOG	FROM	TO LITHO. LO	OG (cont.) <u>or</u> PLU	GGING INTERVALS	
			-				
SEE	ATTACHED LOG)					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged							
under my jurisdiction and was completed on (mo/day/year) .7-16-12							
under the business name of MINTER-WILSON DRILLING CO., INC., by (signature) *** *** *** *** *** *** *** *** *** *							
INSTRUCTIONS: Use ty pewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies							
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. I nclude fee of \$5.00 for each constructed well. Vi sit us at							
http://www.kdheks.gov/wate	http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy							

The Professionals MINTER-WILSON DRILLING CO. Irrigation and Domestic Water Systems Complete Installation

Irrigation and Repairing

INCORPORATED

Phone 620-276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

NAME

DAVE BRYANT

COUNTY

HASKELL

DATE

3-15-12

LOCATION:

SW 1/4 34-29-31 - FROM SOUTHEAST CORNER OF SUBLETTE

7 MILES EAST & 1/4 MILE NORTH

ON THE EAST SIDE

STATIC WATER LEVEL - APPROX, 300 FT.

TEST#4

0' TO 65' - BROWN SANDY CLAY

65' TO 85' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

85' TO 105' - BROWN SANDY CLAY

105' TO 270' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

270' TO 280' - BROWN & BLUE CLAY

280' TO 290' - FINE TO MEDIUM SAND & GRAVEL (BLUE)

290' TO 304' - BLUE CLAY

304' TO 322' - FINE TO MEDIUM SAND & GRAVEL

322' TO 327' - BROWN SANDY CLAY

WITH STRIPS OF SAND & GRAVEL - 20%

327' TO 334' - FINE TO MEDIUM SAND & GRAVEL

334' TO 350' - BROWN & BLUE CLAY

WITH LAYERS OF SAND & GRAVEL - 35%

350' TO 360' - BROWN & BLUE CLAY

360' TO 375' - FINE TO MEDIUM SAND & GRAVEL

375' TO 378' - BROWN SANDY CLAY

378' TO 406' - FINE TO MEDIUM SAND

WITH SOME GRAVEL - 15%

406' TO 441' - BROWN SANDY CLAY

WITH STRIPS OF SAND - 20%

441' TO 443' - FINE TO MEDIUM SAND

443' TO 445' - BROWN SANDY CLAY

445' TO 450' - FINE TO MEDIUM SAND & GRAVEL

450' TO 477' - BROWN SANDY CLAY

477' TO 498' - BROWN & YELLOW CLAY - 20% BROWN ROCK

498' TO 515' - SHALE