		TER WELL RECORD Form		SA 82a-1212		+
LOCATION OF WAT		CI I	Section N			Range Number
ounty: Haskell stance and direction From Sublet.t	from nearest town or city streete, 1 mile West & 9	14 SW 14 SW It address of well if located with the second	thin city?	J T 29	9 s	R 32 E €
WATER WELL OW		od Grain Inc.				·
#, St. Address, Box	#: Box 1184				•	Division of Water Resource
, State, ZIP Code					tion Number:	
OCATE WELL'S LO N "X" IN SECTION	DCATION WITH 4 DEPTH OF Depth(s) Grou	F COMPLETED WELL4				
W SW	WELL'S STATE PE Est. Yield Bore Hole Dia WELL WATEI 1 Domes 2 Irrigatio Was a chemic mitted ASING USED: 3 RMP (SR) 4 ABS 8 5/8!!in. to .435!. A Stainless steel 4 Galvanized steel ATION OPENINGS ARE: 3 Mill slot 4 Key punched ED INTERVALS: From 3	ump test data: Well water water water ameter 15½ in. to	the below last states and the states are supposed to the states are suppose	and surface measured ft. after ft. after ft. after ft., and ly 8 Air condition ply 9 Dewatering only 10 Observation ent? YesNo Water Well Disinfe CASING y below) ft., Dia ft., Dia lbs./ft. Wall thicknes 10 // 12 ft 8 Saw cut 9 Drilled hole 10 Other (spe	on mo/day/yr hours pu hours pu in ing 11 12 well X; If yes, cted? Yes JOINTS: Glued Weld Threa Ss or gauge N Asbestos-ceme Other (specify) None used (op	mping gpm mping gpm . to ft. Injection well Other (Specify below) mo/day/yr sample was sut X No d Clamped ed X aded in. to ft. o 188 ent en hole) 11 None (open hole)
GRAVEL PAG					ft. t	o
GROUT MATERIAL	: 1 Neat cement	2 Cement grout	3 Bentonite	4 Other		
ut Intervals: Fron	n. () ft. to <u>1.</u> 0	† ft., From	ft. to	ft., From	· · · · • · · · · · ·	ft. to
	urce of possible contamination			•		bandoned water well
1 Septic tank	4 Lateral lines		1	Fuel storage		
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12	Pertilizer storage	16 O	ther (specify below)
3 Watertight sew	er lines 6 Seepage pit	9 Feedyard	13	3 Insecticide storage		• • • • • • • • • • • • • • • • • • • •
ection from well?				ow many feet?		
ом то	LITHOLOG SEE ATTACHED LOG		FROM TO)	LITHOLOG	IC LOG
			T			
	OR LANDOWNER'S CERTIFIC,					• •
npleted on (mo/day/ster Well Contractor's	year) 8–24–81	This Water Well F	and the	nis record is true to the pleted on (mo/day/yr)	best of my kn	• •
pleted on (mo/day/ er Well Contractor's er the business nar	year) 8–24–81	This Water Well F	and the Record was come by	nis record is true to the pleted on (mo/day/yr) (signature)	best of my kn 8-28-81	owledge and belief. Kansa

DRILLERS TEST LOG

CUSTOMERS NAME Collingwood Grain Co.	DATE 3-11-80
STREET ADDRESS	TEST # 3
CITY & STATE Sublette, KS. 67877	DRILLER Rector
COUNTY Haskell QUARTER SW SECTION 31 TOWNSHIP	P 29 RANGE 32

				WELL LOCATION
	DRILLED		FOOTAGE	DESCRIPTION OF STRATA STATIC WATER LEVEL
8	FROM	PAY	T	PROPOSED WELL DEPTH
	0		3	TOP SOIL
1127	3		40	BROWN CLAY
	40		80	BROWN CLAY & CALICHE
			1.25	SAND GRAVEL VERY SMALL CLAY STKS.
	125		130	BROWN CLAY
	130	,	149	SAND & GRAVEL SMALL & LARGE
	149		157	BROWN CLAY
	157		177	BROWN CLAY, CALICHE & SAND
-	177		315	SAND FINE TO MED. COARSE & SMALL GRAVEL
7 572	315		320	BROWN CLAY
50	320	35	355	SAND FINE TO MED. COARSE & SMALL GRAVEL
	355	1 1 2 1	365	BLUE CLAY (STICKY)
65	365	27	392	SAND FINE TO MED. COARSE & SMALL GRAVEL
	392	 	405	BROWN CLAY SAND & SMALL LEDGES
60	405	20	425	SAND FINE TO MED. COARSE SMALL GRAVEL CEMENTE
		 		SAND STKS. & LIME STKS: USED WATER
	425	 	470	BROWN CLAY & LIMEROCK (HARD)
	470	1	500	BLUE SHALE & LIMESTONE
-	500	1	640	BLUE SHALE & VERY SMALL SAND STONE
		. 82		
		1		
ļ.,			 	
ļ				total depth - 435'
1,27,72		 	 	set up facing north
				dig pit on the east
		 		dig più on one cabo
		 		install pressure tank north of well
-			 	install pressure tank north of well
7 78. 5.75	 		 	
-	-		 	
		 	 	
	 	177.00	 	
	 		7, 1753 7 Y	
			 	
		-	 	
	 		 	
			 	
			 	
ļ				
L		1		

HENKLE DRILLING & SUPPLY CO., INC.

GARDEN CITY, KANSAS Phone 276-3278 TEST HOLES