

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction		Santing a		Township number	Range number	<del></del> -1	
1. Location of well:	1					20	32		
	Haskell NE 1/4 NE 1/4 S		r —			7 29 s	R 32	<b>₽</b> (W)	
2. Distance and directly 2 E.	lette	i	wner of well:		Gayle Redd				
Street address of well	1	R.R. or street: City, state, zip code:		Sublette, KS					
4. Locate with "X" in section below:  N						6. Bore hole dia. 26 in. Completion date 5-21-7  Well depth 407 ft.			
NW	5-19-76			7 Cable tool Rotary Hollow rod Jetted		se rotary			
Mis. M. I. X.	E					8. Use: Domestic Pu X Irrigation Ai	r conditioning Sto	ck	
sw	SE					<u>Lawn</u> Oi 9. Casing: MateriaStee	Height Abov or be	low	
S 144						Threaded Welded $\underline{X}$ RMP PVC PVC Dio $\underline{16}$ in. to $\underline{407}$ ft. dept		in. _lbs./ft.	
5. Type and color of				From	То	Dia in. to ft. dept	th gage No21	9 -	
- 7,72 3.10 00.01 01				1	,	10. Screen: Manufacturer's n	-		
See	attachment					Type Louvered	Dia. 16"		
						Slot/gauze 1/8" Set between 320	-		
						Gravel pack? Yessize rar	ind	1/8	
						11. Static water level: 235 ft. below land sur		/day/yr.	
						12. Pumping level below land	surfaces:		
						278 ft. after h	nrs.pumping <u>LOUU</u> nrs.pumping	g.p.m.	
						Estimated maximum yield		g.p.m.	
						13. Water sample submitted:  Yes No	mo.,	/day/yr.	
	, , , , , , , , , , , , , , , , , , ,					14. Well head completion: Pitless adapter	2 Inches above s	grade	
				-		15. Well grouted? Yes With: Neat_cement Depth: From ft. to			
						With: Neat cement Depth: From ft. to	BentoniteC	Concrete   -	
						16. Nearest source of possible	e contamination	erved	
						Well disinfected upon comple		No	
						17. Pump: Manufacturer's name	X_ Not installed	-   -   -   -   -   -   -   -   -   -	
						Model number	HP Vol		
	<u> </u>			1-		Length of drop pipe Type:	tt. capacity	.g.p.m. (	
						Submersible	Turbine	1 1	
	(Use a second :	heet if needed)				Jet Centrifugal	Kecipro	Suring S	
18. Elevation: Flat	19. Remarks:					20. Water well contractor's of This well was drilled under m		report	
Topography:						is true to the best of my know Henkle Drlg.	ledge and belief.		
Hill						Business name	Lice	ense No.	
Slope Upland						Signed L. Bot	Garden Cit	- <b>y, ∧</b> \$⊊  5 <b>-10</b> +7(	
Valley						Aufhorized rep	Form WAV	* I	

## DRILLERS TEST LOG

Gayle Redd CUSTOMERS NAME TEST #4 E. Log Hole STREET ADDRESS. DRILLER Lee Sublette, KS CITY & STATE COUNTY Haskell QUARTER SW SECTION 34 TOWNSHIP 29 RANGE 32

Approx. 100' W of the NE corner of the SW 1/4; gas line on LOCATION\_ E end of 1/4

WELL LOCATION

7.	DRILLED		FOOTAGE	Static Water Level
, 4	From	Pay	To	Description of Strata Proposed Well Depth
	00		3	Top soil
	3		64	Brown clay, few caliche st., few sand st.
	64		84	Sand fine med coarse, small to med. gravel. Used
				some water.
	84		91	Brown clay ledges
	91		105	Sand fine med. coarse, few small gravel, few clay
1.7				st.
	105		153	Sand fine med. coarse, small to med. gravel, rough
				in places. Used water. Few large gravel, few
-1"				cemented ledges.
	153		162	Brown clay, ledges, sand st.
	162		200	Sand fine med. coarse, small gravel, few med. Very
				few clay st. Used water.
	200		205	Brown clay, sand st. ledges.
	205		212	Sand fine med., ledges and clay
	212		220	Brown clay, yellow color clay
	220		238	Blue clay
50	238	13	251	Sand fine med. coarse, few small gravel, a few clay
			1	st. Used some water.
	251		266	Gray, tan and brown clay ledges
60	266	62	328	Sand fine med. coarse, small gravel, few clay st.
				Used some water. Stopped drilling to get a load of
				water: blue clay sloughed some when started drilling
				again.
	328		336	Very hard cemented sand, very little clay
<u>_</u>	336		340	Brown clay, sand fine med, coarse, few gravel
60	340	19	359	Sand fine med. coarse, small gravel, very few med.
			,	very few clay st.
3	359	13	372	Brown clay, sand fine med. coarse, small gravel,
				lime rock mixed
3	372	10	382	Cemented sand, a little hard, some clay st., a few
				loose spots
	382		395	Brown clay and lime rock and sand st.
50	395	10	405	Sand fine med. coarse, some small gravel, some clay
	405		480	Brown clay, lime rock ledges, very hard in places,
				few sand st.
		127	·	Pit on south.
			····	TOTAL DEPTH OF WELL 407 FT. Set rig up east.

級HONE 276-3278

MARDIN CITY, KANSAS HENKLE DRILLING & SUPPLY CO., INC. IRRIGATION HEADQUARTERS

SUBLETTE, KANSAS PHONE 675-4311