

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Haskell</u>	$\frac{1}{4}$ $\frac{1}{4}$ NW $\frac{1}{4}$	<u>34</u>	T <u>29</u> S	R <u>32</u> E/W

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: <u>Norman Redd</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # <u>2408 Royal Lytham</u>	Application Number:
City, State, ZIP Code <u>Austin Tx. 78747</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>462</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>302</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping <u>10</u> gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>10</u> in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	Welded
2 PVC	4 ABS	7 Fiberglass	Threaded
Blank casing diameter <u>5</u> in. to <u>44.2</u> ft., Dia. in. to ft., Dia. in. to ft.			
Casing height above land surface <u>24</u> in., weight lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From <u>44.2</u> ft. to <u>462</u> ft., From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>462</u> ft., From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout intervals: From <u>0</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?		How many feet?		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	65	tan sandy clay sand streaks			
65	120	Fine to medium sand			
120	173	coarse sand small gravel clay streaks			
173	180	very sticky clay			
180	202	coarse sand			
202	284	sandy clay sticky			
284	330	sandy clay sand streaks			
330	342	fine to medium sand			
342	410	sandy clay sand streaks			
410	460	white on yellow clay with sand streaks			
	460	Total depth			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12-31-91</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>514</u> This Water Well Record was completed on (mo/day/yr) <u>1-15-92</u> under the business name of <u>Miller Beekhead & Pump</u> by (signature) <u>Everett Miller</u>

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.