

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <b>Haskell</b>	<b>NE 1/4 NE 1/4 NE 1/4</b>	<b>27</b>	<b>T 29 S</b>	<b>R 32 EW</b>

Distance and direction from nearest town or city street address of well if located within city?

East side of Sublette 2 East 1/8 South West into blue house

2 WATER WELL OWNER: SW Windmill John Wall

RR#, St. Address, Box # : P.O. Box 909

City, State, ZIP Code : Meade, KS 67864

Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 500 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1 346 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 346 ft. below land surface measured on mo/day/yr 8-2-05 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <b>X</b> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <b>X</b> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <b>X</b> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 360 ft. Dia			Threaded
Casing height above land surface 24 in., weight 3.706 lbs./ft. Wall thickness or gauge No SDR 21.316			
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	7 PVC	10 Asbestos-Cement
1 Steel	3 Stainless Steel	8 RMP (SR)	11 Other (Specify)
2 Brass	4 Galvanized Steel	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 360 ft. to 500 ft. From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 260 ft. to 500 ft. From ft. to ft. From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other Hole plug
Grout Intervals: From 1 ft. to 25 ft. From ft. to ft. From ft. to ft. From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?			13 Insecticide storage	
			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	7	Clay	285	305	Course sand
7	45	Caliche clay	305	325	Tight sand
45	55	Caliche clay	325	330	Clay
55	65	Sandy clay/ sand	330	365	Tight sand
65	83	Course sand	365	375	Sandy clay
83	87	Clay	375	390	Tight sand
87	105	Sand with clay streaks	390	410	Tight sand with clay streaks
105	120	Sand	410	453	Caliche clay
120	144	Small gravel	453	462	Sand
144	146	Clay	462	477	Sandy clay with streaks of sand
146	165	Sand	477	485	Clay
165	184	Medium gravel	485	495	Sand
184	192	Clay	495	500	Black clay
192	285	Course sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-2-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No KWWCL-430 This Water Well Record was completed on (mo/day/yr) 8-2-05 under the business name of Howard Drilling Co Box 806 Beaver, Ok 73932 by (signature) <i>Howard Drilling Co</i>
--