

1 LOCATION OF WATER WELL:		Fraction <u>NW</u> <u>SW</u> <u>SW</u> <u>SW</u>	Section Number <u>32</u>	Township Number <u>T 29 S</u>	Range Number <u>R 32 E</u>
County: <u>Haskell</u>					
Distance and direction from nearest town or city street address of well if located within city? <u>N Hwy 83</u>					
2 WATER WELL OWNER: <u>Collingwood Grain</u>					
RR#, St. Address, Box # : <u>N Hwy 83</u>			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : <u>Sublette KS</u>			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>380</u> ft. ELEVATION: <u>2937.93</u>			
		Depth(s) Groundwater Encountered 1 <u>357</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 <u>Monitoring well</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 <u>PVC</u>		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
Blank casing diameter <u>4</u> in. to <u>330</u> ft. Dia		7 Fiberglass	Threaded		
Casing height above land surface <u>3</u> in. weight		lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless Steel	5 Fiberglass	8 <u>PVC</u>	10 Asbestos-Cement
2 Brass		4 Galvanized Steel	6 Concrete tile	8 RMP (SR)	11 Other (Specify)
				9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	ft.
SCREEN-PERFORATED INTERVALS: From <u>330</u> ft. to <u>380</u> ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>327</u> ft. to <u>380</u> ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 <u>Bentonite</u> 4 Other					
Grout Intervals: From <u>322</u> ft. to <u>322</u> ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 <u>Other (specify below)</u>
				13 Insecticide storage	<u>LUST Site</u>
Direction from well? <u>NW</u>				How many feet? <u>15</u>	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	White Rock			
0.5	40	Clay, red brown			
40	92	Sandy Clay, tan			
92	140	Gravel, red/tan/brown			
140	150	Sand, red/tan/brown			
150	180	Gravel, red/tan/brown			
180	185	Sandy clay, brown/grey			
185	280	Gravel, red/brown/black			
280	352	Shale, grey			
352	400	Sand/tan			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3/15/06</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>594</u> This Water Well Record was completed on (mo/day/yr) <u>3/28/06</u> under the business name of <u>Corance Great Plains</u> by (signature) <u>[Signature]</u>					