WATER WELL RECORD	Form WWC-5	Division of Water	er Resources; App. No.└		
1 LOCATION OF WATER WELL: County: Haskel1	Fraction SW 1/4 SE 1/4 NW 1/4	Section Number 25	Township Number T 29 S	Range Number R 32 EW	
Distance and direction from nearest town or city street address of well if Global Positioning Systems (decimal degrees, min. of 4 digits)					
located within city? From SE corner of Sublette-4 miles E, Latitude:					
1 mile N, 2,825 ft. north & 3,725		Longitude:			
2 WATER WELL OWNER: McClure F RR#, St. Address, Box # : HC 1 - Bo	amily Trust	Elevation:			
	KS 67877	Datum:			
		Data Collection			
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL540					
LOCATION WITH AN "X" IN Depth(s) Groundwater	Encountered (1)	ft (2)	ft (3)	ft	
SECTION BOX: WELL'S STATIC WA					
N Pump test data	Pump test data: Well water wasft. after hours pumping gpm				
	Est. Yieldgpm: Well water wasft. afterhours pumpinggpm				
NW NE 1 D 1 2 E					
W X Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2) Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs					
Sample was submitted					
S					
5 TYPE OF CASING USED: 5 Wrought	Iron 8 Concrete tile	CASIN	IG JOINTS: Glued		
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) WeldedXX					
2 PVC 4 ABS 7 Fiberglass					
Blank casing diameter 16 in to 360 ft., Diameter in to ft., Diamet					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)					
2 Brass 4 Galvanized Steal 6 Cond	. ,	Asbestos-Cement	12 None used (oper	hole)	
SCREEN OR PERFORATION OPENINGS AR				• `	
1 Continuous slot (3) Mill slot 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched (6) Wire wrapped 8 Saw Cut 10 Other (specify)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)					
From ft. to ft. From ft. to ft.					
From					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to	20 ft., From	ft. to	ft From	ft. toft.	
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well Direction from well? How many feet?					
Direction from well? LITHOLOGIC			PLUGGING INT		
FROM TO ETHIOLOGIS	C LOG TRO	IVI TO	TEOGOING INT	EKVALS	
See attached	log				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged					
under my jurisdiction and was completed on (mo/day/year) 6-8-96 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No 208 This Water Well Record was completed on (mo/day/year) 6-29-06					
under the business name of Minter-Wilson Drilling Co., Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone					
785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at					
http://www.kdhe.state.ks.us/geo/waterwells.					

MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

INCORPORATED

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

McClure Family Trust Haskell County 2-28-06

552' to 560' - Red bed

Location: NW $\frac{1}{4}$ 25-29-32 - From east side of Sublette - 3 miles northeast on Hwy. 56 - $\frac{1}{4}$ mile south & $\frac{1}{4}$ mile east to pivot

Static Water Level - 300 Ft.

Test #3

0' to 3' - Top soil 3' to 38' - Brown clay 38' to 53' - Brown sandy clay 53' to 63' - Fine sand 63' to 74' - Fine to medium sand & gravel 74' to 77' - Gray clay 77' to 81' - Fine to medium sand & gravel 81' to 87' - Brown sandy clay 87' to 97' - Brown clay 97' to 160' - Fine to medium sand & gravel 160' to 166' - Brown clay 166' to 194' - Fine to medium sand & gravel 194' to 204' - Brown clay 204' to 223' - Brown clay - small gravel strip 223' to 245' - Fine to medium sand & gravel 245' to 272' - Brown clay 272' to 281' - Blue clay 281' to 303' - Brown blue clay mixed 303' to 354' - Brown clay - small gravel strips 354' to 413' - Fine to medium sand & gravel 413' to 425' - Fine to medium sand & gravel - clay streak - tight 425' to 449' - Fine to medium sand & gravel - 10% clay streak 449' to 455' - Brown clay 455' to 494' - Brown sandy clay 494' to 510' - Brown sandy clay 510' to 525' - Brown rock - loose 525' to 540' - Yellow clay 540' to 552' - Yellow gray clay