USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

K. 1 5.

	County	Fraction		Section number		Township number	Range number	
1. Location of well:	Haskell	SE 1/4 NE 1/4 S	-			r 29 s	R 33	
	ction from nearest town or city: 5-3/4 N of Subl location If in city:	ette, KS	R.R. or		6	ck Trimpa 05 S. Wooten Sublette, KS	67877	
4. Locate with "X"		Sketch map:				6. Bore hole dia. 26 in Well depth 546 ft.	. Completion date	75
NW	 NE	7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored X_ Reverse rotary						
w X	E					8. Use: Domestic P XIrrigation A Lawn C	ir conditioning Sta	
SW3	SE					9. Casing: Material Stee Threaded Welded _X RMP PVC		elow in. _lbs./ft.
-	lile					Dia 16 in. to 546ft. de	oth!Wall Thickness: in	ches or
5. Type and color of	material			From	То	Dia in. to ft. dep 10. Screen: Manufacturer's		
See 2	Attachment					W. A. Brown Type Leuvered		
		•				Slot/gguze 1/8"	Length 120	
	····					Set between 545 435 ft.	_ft. and <u>465</u> and <u>355</u>	ft.
	· · · · · · · · · · · · · · · · · · ·					Gravel pack YES Size ro	ange of material <u>청</u>	
		4.00				11. Static water level: 248 ft. below land su	rface Date 12/2	./doy/уг. 26 <u>/7</u> 5
						12. Pumping level below lan	d surfaces:	
						306 ft. after		
				-		Estimated maximum yield-		g.p.m.
	w			<u> </u>		13. Water sample submitted: Yes No	mo Date	./day/yr.
						14. Well head completion:		
						Pitless adapter	12 Inches above	grade
						15. Well grouted? <u>Yes</u> With: Neat cement X	Bentonite	Concrete
				+		Depth: FromO ft. to		
						16. Nearest source of possib	le contamination:	none served
						Well disinfected upon comp	etion?Yes	No
	*******					17. Pump: Manufacturer's name	X Not installed	7
	· · · · · · · · · · · · · · · · · · ·			+		Model number	HP Vo	its
				-	ļ	Length of drop pipe Type:	ft. capacity	_g.p.m.
						Submersible	Turbin	
	(Use a secon	d sheet if needed)				Jet Centrifugal	Recipr	ocating
18. Elevation:	19. Remarks:			. 4	1	20. Water well contractor's	certification:	· · · · · · · · · ·
Flat						is true to the best of my kno		· ·
Topography:		Henkle DRIG & Supply 145						
Hill Slope						Business name Address BOX 639	<u> gardenCit</u>	Y KS
Upland						Signed & L. Both	Date Date	1-15-7
Valley						Authorized re	presentative	

DRILLERS TEST LOG

CUSTOMERS NAME	Nick Trimpa	DATE 12-15-75
	605 South Wooten	TEST # 1 E-Log 580'
		DRILLERRector
COUNTY Haskell	QUARTER SW SECTION 8	8 TOWNSHIP 29 RANGE 33

LOCATION 1320' South of NE corner of the 1/2.

				WELL LOCATION
%	DRILLED)	FOOTAGE	Static Water Level
	From	Pay	cT	Description of Strata Proposed Well Depth
	0		3	Top soil
	3		48	Brown clay
	48		208	Sand & gravel (ragged in places) used water.
	208		220	Brown & blue clay
	220		276	Blue clay (sticky)
55	276	16	292	Sand fine to med coarse & small gravel
	292		300	Blue clay
55	300	20	320	Blue sand fine to med coarse & small gravel, loos
				used water, very fine clay st.
65	320	33	353	Sand fine to med coarse, small gravel, loose, use
				water, dark brown in color
	353		359 ·	Brown clay & limerock
70	359	13	372	Sand fine to med coarse & small gravel, loose, us
			,	lots of water (good)
	372		396	Brown clay, limerock & sand
60	396	39	435	Sand fine to med coarse & small gravel, firm in
				places, loose in places, used water.
	435		465	Brown clay & limerock (clay sticky)
70	465	75	540	Sand fine to med coarse, small gravel, loose, use
				lots of water, good.
75	540	7	547	Brown sand & gravel, brown & tan rock & few white
				rock, ragged, used lots of water.
	547		560	Yellow clay & soapstone
	560	1	580	Blue shale
		203		
·				TOTAL DEPTH OF WELL 547'
		 -		Set up face S P
		1		Set up face S.E. Pit on the South
		1		Set pump motor for well on east side of well
		1		Sec bamb mores for well ou east side of well
	·	-		4
		-	 	
-		+	 	
-		+	 	

HONE 276-3278 .

ARDEN CITY, KANSAS HENKLE DRILLING & SUPPLY CO., INC. SUBLETTE, KANSAS IRRIGATION HEADQUARTERS

PHONE 675-4311