

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Haskell		NE 1/4 NE 1/4 NW 1/4	22	T 29 S	R 33 E/W
Distance and direction from nearest town or city street address of well if located within city? From Junction 56 & 83 near Sublette - 2 Miles North, 2 Miles West, 4930 Ft./North & 2730 Ft. West					
2 WATER WELL OWNER:		Ruby Powell			
RR#, St. Address, Box # :		P. O. Box 729			
City, State, ZIP Code :		Sublette, Kansas 67877			
		Board of Agriculture, Division of Water Resources Application Number: 25,601			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 685 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 346 ft. below land surface measured on mo/day/yr 3-20-91			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 30 in. to 685 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded X
			7 Fiberglass		Threaded
Blank casing diameter 16 in. to 600 ft., Dia. 20 in. to 430 ft., Dia. 20 in. to 620 ft.					
Casing height above land surface 12 in., weight 16"-42.05 lbs./ft. Wall thickness or gauge No. 250					
TYPE OF SCREEN OR PERFORATION MATERIAL: 20"-52.73					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: 20' From 360 ft. to 430 ft., From 475 ft. to 525 ft.					
16" From 600 ft. to 620 ft., From 620 ft. to 685 ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 295 ft., From 355 ft. to 685 ft.					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From 0 ft. to 20 ft., From 295 ft. to 355 ft., From 14 ft. to					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	
Direction from well? Northeast		How many feet? 290 ft. north & 30 ft. east			
FROM	TO	LITHOLOGIC LOG		FROM	TO
		See attached log			
		PLUGGING INTERVALS			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-3-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 5-23-91 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Keller					