


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: HASKELL	NC 1/4 NW 1/4 SE 1/4	32	T 29S S	R 33W E
Distance and direction from nearest town or city street address of well if located within city?				

4 WEST OF SUBLETTE 1 1/2 NORTH 1/4 WEST INTO LOC.

2 WATER WELL OWNER: **HARRIS OIL & GAS**
RR#, St. Address, Box #: **1125 17th ST STE 2290**
City, State, ZIP Code: **DENVER, CO. 80202**

#1-32 *Blair-Williams*
Board of Agriculture, Division of Water Resources
Application Number: **940112**

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 440 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 350 ft. 2. 350 ft. 3. 350 ft. WELL'S STATIC WATER LEVEL 350 ft. below land surface measured on mo/day/yr 3-19-94 Pump test data: Well water was 370 ft. after 1 hours pumping 80 gpm Est. Yield 80 gpm: Well water was 370 ft. after 1 hours pumping 80 gpm Bore Hole Diameter 11 in. to 440 ft. and 11 in. to 440 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 6 in. to 440 ft. Dia 6 in. to 440 ft. Dia 6 in. to 440 ft.			
Casing height above land surface 24 in. weight 2.902 lbs./ft. Wall thickness or gauge No. 316 SDR 21			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 360 ft. to 440 ft. From 360 ft. to 440 ft. From 360 ft. to 440 ft.			
GRAVEL PACK INTERVALS: From 240 ft. to 440 ft. From 240 ft. to 440 ft. From 240 ft. to 440 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	HOLE PLUG
Grout Intervals: From 1 ft. to 20 ft. From 1 ft. to 20 ft. From 1 ft. to 20 ft.					
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	13 Insecticide storage	
Direction from well? Northeast			How many feet? 150		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	TOP			
3	20	CLAY			
20	80	SANDY CLAY			
80	297	SAND & GRAVEL			
297	344	CLAY			
344	369	SAND			
369	380	BLACK			
380	420	SAND			
420	440	BLUE CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was **(1)** constructed, **(2)** reconstructed, or **(3)** plugged under my jurisdiction and was completed on (mo/day/year) **3-19-94** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **KWWCL-430**. This Water Well Record was completed on (mo/day/yr) **3-19-94** under the business name of **HOWARD DRUG CO BOX 806 BEAVER, OK 73932** by (signature) *Alva Howard*

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.