T : 00 : =:				H WELL HE	COHD	Form WWC-		2a-1212				
LOCATION OF WATER WELL:			Fraction	N/=		1./	ction Numbe	1 '	Number	1	Number	
County: HASKEL			NE 1/4		1/4	1/4	_33	J T 29	s s	I R	33 E(W	
Distance ar	nd direction	from nearest town of	or city street ac	ddress of w	ell if locat	ed within city?					_	
FROM	SUBLETT	E 3 MILES W	EST. ½ NO	ORTH WES	ST INT	O LOC.						
									#1*33 P	REEDY		
WATER WELL OWNER: HARRIS OIL & GAS RR#, St. Address, Box # : P.O. BOX 976								Board of Agriculture, Division of Water Resources				
City, State,				\E					tion Number:		2/7	
		LIBERAL								170	~ 1. (
AN "X"	NELL'S LO	DCATION WITH 4 De						/ATION: . 2				
т Г	1	I WE	ELL'S STATIC	WATER LI	EVEL	350 ft.	below land s	urface measured	on mo/dav/vr	8+11+	•94	
I	1	1 1				-		after 1.				
-	- NW	NE									•	
1	. !							after				
≗ w ⊢	1	■ F Bo	ore Hole Diame	eter + L	in. to	o 440		, and	ir	. to	.	
≨ "	! XI	! WE	ELL WATER T	O BE USE	D AS:	5 Public wat			ing 11	Injection well		
7	s.,,	SE	1 Domestic	3 Fe	edlot	6 Oil field w	ater supply	9 Dewatering	12	Other (Specific	y below)	
	- 3₩	3	2 Irrigation	4 Inc	dustrial	Lawn and	garden only	10 Monitoring	well,			
	- ; - 1	Wa	as a chemical/b	pacteriologic	cal sample	submitted to [Department?	YesNo		. mo/dav/vr sa	mple was s	
<u> </u>			tted	•				Vater Well Disinfe		X No		
TYPE	E BI ANK C	ASING USED:		5 Wrough	t iron	8 Conc				d X Clar	mned	
_				•								
1 Ste		3 RMP (SR)		6 Asbesto			(specify be	•		led		
(2)°V		4 ABS		7 Fibergla						aded		
Blank casir	ng diameter	6 in.	to440	ft., [Dia	in. t	o <i></i> .	ft., Dia		in. to		
Casing heigh	ght above la	and surface 2	4	.in., weight	2	902 <u></u>	lb	s./ft. Wall thickne	ss or gauge N	ю 316 .	SDR. 21	
TYPE OF	SCREEN O	R PERFORATION M	MATERIAL:			(7)	VC	10	Asbestos-cem	ent		
1 Ste		3 Stainless st		5 Fibergla	926	8.8	MP (SR))		
2 Bra		4 Galvanized		6 Concre		9 A						
				o Concre			33		None used (or	•		
		RATION OPENINGS				zed wrapped		8 Saw cut		11 None (o	pen noie)	
1 Co	ntinuous slo	t 3 Mills	slot		6 Wire	e wrapped		9 Drilled hol	es			
2 Lou	vered shutt	er 4 Key j	punched		7 Tore			10 Other (spe	• •			
SCREEN-F	PERFORATE	D INTERVALS:	From 3.6	50	ft. to	440	ft., F	rom	ft.	to		
			From		ft. to		ft F	rom	ft.	to		
G	BAVEL PA	CK INTERVALS:						rom				
•		5	From	-0	ft. to		ft., F		ft.			
CDOUT	MATERIAL	. 1 Neat cerr		0.0				4 Other I			-	
_				2 Cement	-			,				
Grout Inter	vals: From	n 1 ft.	to20	ft., f	rom	ft.	to	ft., From		ft. to		
What is the	e nearest so	ource of possible cor	ntamination:				10 Liv	estock pens		Abandoned wa		
1 Se	ptic tank	4 Lateral li	ines	7 1	Pit privy		11 Fu	el storage	(15)	Dil well/Gas w	ell	
2 Se	wer lines	5 Cess po	ool	8 9	Sewage la	igo on	12 Fe	rtilizer storage	16 (Other (specify	below)	
3 Wa	atertight sew	er lines 6 Seepage	e pit	9 (eedvard			ecticide storage				
Direction fr	•	NORTHEAST			,			nany feet?	150			
FROM	TO		LITHOLOGIC	LOG		FROM	TO	idily idet:	PLUGGING	INTERVALS		
						337		MED CDAY				
0	2	TOP CLAY							VEL			
2	27	CLAY & CALI				342						
27	52	SANDY CLAY	& CLAY			249	367	SAND & G	RAVEL			
52	61	CALICHE & C	LAY			367	384	SAND & L	ARGE GRAV	ÆL		
61	74	SANDY CLAY				384						
74	85	COARSE SAND	& CLAY			402	1			AV CUDEN	KC	
85	95	COARSE SAND					_	1		MINITE INCA		
						413						
95	104	SANDY CLAY				425	440	BLUE CLA	Υ			
104	141	COARSE SAND										
141	208	SAND & SMAI	L GRAVEL									
208	221	MED. GRAVEL	4									
221	237	BLAK SANDY										
237	282	COARSE SANS										
282	315	CLAY & GRAV		···								
315	337	GRAVEL & CI										
7 CONTR	RACTOR'S	OR LANDOWNER'S	CERTIFICATI	ION: This v	vater well	was (1) onsti	ucted, (2) re	econstructed, or ((3) plugged ur	der my jurisdi	iction and v	
completed	on (mo/day	/year) 8 ÷11	L ≈ 94					cord is true to the				
		s License No K		-	nia Matar	Wall Decord w					\bigcirc	
			(MMCT¥420	10	us water	well necord v	as combine	CO ON (INO/CIAV/SP)				
							-		1/2-		12	
under the	business na	me of HOWARD D	ORLG.CO.BC	OX 806	BEAVER	OK 7393	2 by (sig	nature)	las	Terra	ud	