

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: HASKELL		C 1/4 NE 1/4 NE 1/4		27		T 29 S		R 34W EW	
Distance and direction from nearest town or city street address of well if located within city?									
4 1/2 MILES NORTHWEST SATANTA, KS									
2 WATER WELL OWNER: DUNNE EQUITIES									
RR#, St. Address, Box #: 8100 E. 22nd. ST N STE 1100						Board of Agriculture, Division of Water Resources			
City, State, ZIP Code: WICHITA, KS 67226						Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 460 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. 265 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 265 ft. below land surface measured on mo/day/yr 1-9-95							
		Pump test data: Well water was 280 ft. after 1 hours pumping 85 gpm							
		Est. Yield 85 gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 11 in. to 460 ft. and in. to ft.							
WELL WATER TO BE USED AS:									
1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below) 10 Monitoring well									
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes X No									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded									
Blank casing diameter 6 in. to 460 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface 24 in. weight 2.902 lbs./ft. Wall thickness or gauge No. 280 SDR 21									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 340 ft. to 460 ft. From ft. to ft. From ft. to ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 320 ft. to 460 ft. From ft. to ft. From ft. to ft. From ft. to ft.									
6 GROUT MATERIAL:									
1 Neat cement 2 Cement grout 3 Bentonite 4 Other HOLE PLUG Grout intervals: From 9 ft. to 20 ft. From ft. to ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage									
Direction from well? Southeast How many feet? 200									
FROM TO LITHOLOGIC LOG					FROM TO PLUGGING INTERVALS				
0	2	TOP	330	337	SANDY CLAY				
2	18	CLAY	337	346	SAND				
18	29	SANDY CLAY	346	376	SANDY CLAY				
29	63	SAND & GRAVEL	376	389	SAND				
63	67	SANDY CLAY	389	416	SANDY CLAY				
67	172	SAND & GRAVEL	416	460	FINE SAND W/SANDY CLAY STREAKS				
172	203	GRAVEL W/CLAY STREAKS							
203	218	CLAY							
218	227	SAND							
227	232	SANDY CLAY							
232	249	TAN CLAY							
249	270	SAND W/BLUE CLAY STREAKS							
270	310	BLUE CLAY							
310	321	SAND & SMALL GRAVEL							
321	330	TAN CLAY							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-9-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 1-9-95 under the business name of HOWARD DRLG. CO. BOX 806 BEAVER, OK 73932 by (signature) Howard DRLG.									