

USE TYPEWRITER OR BALL
POINT PEN—PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment—Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Haskell	Fraction SW 1/4 NE 1/4 NE 1/4	Section number 16	Township number T 29 S R 34	Range number 34
2. Distance and direction from nearest town or city: 3 N. of Sublette Street address of well location if in city: on Hiway 83, 9 1/2 W., 5/8 N.		3. Owner of well: R.R. or street: City, state, zip code:		Courtney Roberts R.F.D. Satanta, Kansas 67870		
4. Locate with "X" in section below: N W E S 1 Mile Sketch map:		6. Bore hole dia. 26 in. Completion date 3-10-77 Well depth 600 ft.		7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
5. Type and color of material		8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		9. Casing: Material steel Height: Above surface Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 16 in. to 601 ft. depth Wall Thickness: inches or Dia. 16 in. to 601 ft. depth gauge No. 250		
		10. Screen: Manufacturer's name Johnson		Type galv. Dia. 16" Slot 1/8" Length 20 ft. 60" Set between 480 ft. and 540 ft. Perf: 320-480 and 540-600 ft. Gravel pack? yes Size range of material 3" down		
		11. Static water level: 278 ft. below land surface Date 2-11-77		12. Pumping level below land surfaces: 328 ft. after 4 hrs. pumping 1350 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 1350 g.p.m.		
		13. Water sample submitted: Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date		14. Well head completion: 12 inches above grade <input type="checkbox"/> Pitless adapter		
		15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		16. Nearest source of possible contamination: N/A ft. Direction Type Well disinfected upon completion? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>		
(Use a second sheet if needed)		17. Pump: Not installed Manufacturer's name Goulds Model number 15-15M HP 200 Volts Length of drop pipe 440 ft. capacity 1600 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter-Wilson Drlg. Co. 208 Business name License No. Address Box A Garden City, Ks. Signed [Signature] Date 3-30-77 Authorized representative		
18. Elevation: Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley		19. Remarks:				

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

TEST HOLE LOG

Wagner's

Box 10, Ulysses, Kansas 67880

Water Wells & Test Holes

Phone (316) 356-2396

Date 1-18-1977Test No. 2Qtr. NE Sec. 16Twp. 29 Rge. 34Co. HaskellLand Owner Courtney RobertsAddress Satanta, Kansas

CONSOLIDATED-SALINA

FOOTAGE	Description of Strata
0 - 20	Surface & fine sand
20 - 40	Gyp & brown clay
40 - 60	Fine sand
60 - 80	Sand
80 - 100	Brown clay
100 - 140	Sand
140 - 160	Brown clay
160 - 200	Sand
200 - 280	Brown clay: Some fine sand 270-280
280 - 320	Blue clay
320 - 420	Coarse sand
420 - 440	Brown clay
440 - 480	Fine sand
480 - 540	Coarse sand
540 - 560	Brown clay - Dakota
560 - 580	" " " " "

Hole at 580 ft.

Drill hole 600 ft.

0 - 320
 320 - 480
 480 - 540
 540 - 600