

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Haskell		NW 1/4 NE 1/4 SW 1/4		34		T 29 S		R 34 E/W	
Distance and direction from nearest town or city street address of well if located within city? From west side of Satanta - 1-3/4 Miles North, 2 Miles West, 1 Mile North, 1,660 Ft. East and 2,100 Ft. North									
2 WATER WELL OWNER:		Mesa Limited Partnership				Boring # 9248			
RR#, St. Address, Box #:		P. O. Box 2009				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code:		Amarillo, Texas 79189				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 382		5. ELEVATION:					
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 300 ft. below land surface measured on mo/day/yr 10-5-92							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 9-7/8 in. to 382 ft., and in. to ft.							
WELL WATER TO BE USED AS:		5 Public water supply		8 Air conditioning		11 Injection well			
1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering		12 Other (Specify below)	
2 Irrigation		4 Industrial		7 Lawn and garden only		10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes No X									
5 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued X Clamped			
1 Steel		3 RMP (SR)		6 Asbestos-Cement		Welded			
2 PVC		4 ABS		7 Fiberglass		Threaded			
Blank casing diameter 5 in. to 332 ft., Dia. in. to ft., Dia. in. to ft.									
Casing height above land surface 12 in., weight 3.43 lbs./ft. Wall thickness or gauge No. 327									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC		10 Asbestos-cement					
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)		11 Other (specify)	
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut		11 None (open hole)			
1 Continuous slot		3 Mill slot		6 Wire wrapped		9 Drilled holes			
2 Louvered shutter		4 Key punched		7 Torch cut		10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 332 ft. to 382 ft.		From ft. to ft.					
		From ft. to ft.		From ft. to ft.					
GRAVEL PACK INTERVALS:		From 24 ft. to 382 ft.		From ft. to ft.					
		From ft. to ft.		From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement		2 Cement grout		3 Bentonite		4 Other	
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens		14 Abandoned water well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage		15 Oil well/Gas well	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage		16 Other (specify below)	
						13 Insecticide storage		n/a NONE	
Direction from well?						How many feet?			
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS			
		See attached log							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-1-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 7-15-93 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Keller									