			· · · · · · · · · · · · · · · · · · ·	R WELL RECC	HD For	m WWC-5	KSA 828			r		
LOCATION OF WATER WELL:			Fraction	A/W)	SE	Section	on Number	· ·	Number		Number	
County: HASKELL.  Distance and direction from nearest town of			1/4				10	T 29	) S	<u>  R 34</u>	4 E/W	
			· ·									
FROM	SATANTA	STRAIGHT N	ORTH 6 3 M	AILES 戋 W	EST 3/8	NORTH.	EAST I	NTO LOC.				
WATER	WELL OW	NER: ANADAR	KO PETROLE	eum					WHITE "C			
RR#, St. A	ddress, Box	# : P.O. B	OX 351	X 351					Board of Agriculture, Division of Water Resources			
City, State,	ZIP Code		L. KANSAS	67901				Applica	tion Number:	940	465	
LOCATE AN "X" II	WELL'S LO	CATION WITH	DEPTH OF C	OMPLETED W								
	<del></del>		Depth(s) Ground									
1	i 1		WELL'S STATIC		, -							
	- NW	NE						after $\dots$ $1$ .	•	· -		
J	- 1		Est. Yield 8	•								
₹ w  -			Bore Hole Diame									
₹	- !	<b>X</b> !   V	WELL WATER T	O BE USED A		Public water		8 Air condition	ū	Injection well		
ī L.	_ swl	SE	1 Domestic	3 Feedle				9 Dewatering		Other (Specify		
	1	. 1	2 Irrigation	4 Indust	trial 7 L	awn and ga	rden only	10 Monitoring	well,			
1 L	1	IV	Nas a chemical/t	bacteriological s	sample subr	nitted to Dep	artment? Y	'esNo.	$X$ $$ ; If yes,	, mo/day/yr sa	mple was sub	
<u> </u>	<u> </u>	n	mitted				Wa	ater Well Disinfo	ected? Yes	X No		
5 TYPE O	F BLANK C	ASING USED:		5 Wrought in	on	8 Concrete	e tile	CASING	JOINTS: Glued	d . 🗶 Clar	nped	
Ste	el	3 RMP (SR)	)	6 Asbestos-C	Cement	9 Other (s	pecify belo	w)	Weld	ed		
(2) V	0	4 ABS		7 Fiberglass					Threa	aded		
Blank casin	g diameter	<u>. 6</u> ir	n. to 520	ft., Dia		in. to .		ft., Dia		in. to	ft.	
Casing heigh	ht above la	nd surface2	4	.in., weight	2,902		Ibs.	./ft. Wall thickne	ss or gauge N	o 316	SDR 21	
		R PERFORATION				7 VC			Asbestos-ceme			
1 Ste	el	3 Stainless	teel 5 Fiberglass			8 RMP	(SR)	11 Other (specify)				
2 Bra	SS	4 Galvanize		6 Concrete ti	ile	9 ABS			None used (op			
		ATION OPENING	S ARE:		5 Gauzed v	wrapped		8 aw cut	٠,	11 None (o	pen hole)	
	ntinuous slo				6 Wire wra	• •		9 Drilled ho		•		
	vered shutt		y punched		7 Torch cut	• •			ecify)			
		D INTERVALS:					ft Fro	om				
OOTILLIAT	LIN ONATE	D WILLIAMES.						om				
G	DAVEL DA	CK INTERVALS:					,	om				
u	HAVEL FA	JR INTERVALS.	From		ft. to	J20	ft., Fr		ft. 1		ft.	
6 GROUT	MATERIAL	: 1 eat ce		2 Cement gro		3 Benton		OtherH				
Grout Inten			t. to 20 .	•				,				
		urce of possible c						stock pens		bandoned wa		
		•		7 Dit .	orivo.			-				
1 Septic tank 4 Lateral li 2 Sewer lines 5 Cess po				• •			11 Fuel storage			15 Other (appoint helps)		
		5 Cess p		5 5			12 Fertilizer storage 16 Other (specify below)					
	•	er lines 6 Seepa	ge pit	9 Fee	ayara			cticide storage	9/11			
Direction fr		<b>_</b>	LITHOLOGIC	100	T	FROM		any feet?	PLUGGING I	INTERVALS		
FROM	то		LITHOLOGIC	LOG			то		reoddiid	INTERVALS		
0	2	TOP CLAY				208	215	CLAY				
2	8	CLAY				215	222	SM. GRAVI				
8	18	CALICHE CI	AY			222	274	CLAY				
18	32	CALICHE				274	285	SAND				
32	39	SANDY CLAY				285	293	CLAY				
39	63	COARSE SAN				293	313	BLUE CLA				
63	76	COARSE SAN	ND SMALL G	RAVEL		313	321	COARSE S	AND			
76	95	SANDY CLAY	ζ			321	326	CLAY				
95	121	MED. GRAVE	EL			326	352	COARSE S	AND			
121	126	CLAY				352	369	SM. GRAV				
126	142	COARSE SAN	AD			369	405	COARSE S				
142	156	SANDY CLAY				405	428	l	AND TO ME	D. GRAVE	L	
156	174	COARSE SAN				428	452	SAND				
174	180	MED. GRAVE				452	460		LE & SAND			
180	185					460		MED. GRA				
			O OFFICIAL	ION. This						dor multiple	iotion and	
		OR LANDOWNER		ION: This wate	er well was							
		/year) 8 <del>+</del> 25		· · · · · · · · · · · · · · · · · · ·				cord is true to th			Dellet, Kansas	
		s License No								110		
under the t	business na	me of HOWARD	_DRLG.CO.F	30X 806 BI	EAVER, (	JK 73932	by (sign	ature)		VUL		
		pewriter or ball point pe							ers. Send top three one for your record		s Department	