

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: STANTON		S2 1/4 SE 1/4 NW 1/4	28	T 29S S	R 39W E/W
Distance and direction from nearest town or city street address of well if located within city?					
4 1/2 MILES SOUTHWEST BIG BOW, KS					
2 WATER WELL OWNER:		#1-28-R&L FARMS			
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Application Number: #930442			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 380 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 180 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 180 ft. below land surface measured on mo/day/yr 11-9-93			
		Pump test data: Well water was 273 ft. after 1 hours pumping 100 gpm			
		Est. Yield 100 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 1/2 in. to 380 ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes <input checked="" type="checkbox"/> No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter 5 in. to 380 ft. Dia		7 Fiberglass Threaded			
Casing height above land surface 24 in., weight 2.902 lbs./ft. Wall thickness or gauge No. 280 SDR 21					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 260 ft. to 380 ft.		From ft. to ft.			
GRAVEL PACK INTERVALS: From 240 ft. to 380 ft.		From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		HOLE PLUG			
Grout Intervals: From 1 ft. to 20 ft.		From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? SOUTHEAST		How many feet? 200'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	FINE SAND			
10	60	SANDY CLAY			
60	75	COARSE SAND			
75	100	SANDY CLAY			
100	160	CLAY			
160	170	SANDY CLAY			
170	210	FINE TO COARSE SAND STREAKS OF CLAY AT 200			
210	240	SANDY CLAY			
240	280	FINE TO COARSE SAND			
280	303	SANDY CLAY			
303	370	FINE TO COARSE SAND & GRAVEL			
370	380	BROWN & BLUE CLAY			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-9-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 11-9-93 under the business name of HOWARD DRLG, CO, BOX 806 BEAVER, OK 73932 by (signature)					

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.