

1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number	Range Number
County: Stanton		NE ¼ NW ¼ NW ¼	34		T 29 S	R 40 EW

1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number	Range Number
County: Stanton	NE ¼ NW ¼ NW ¼	34	T 29 S	R 40 E	W	

Distance and direction from nearest town or city street address of well if located within city?

From southeast corner of Johnson - 6 miles south, 4 miles east, 5,160 ft. north & 4,410 ft. w.

2	WATER WELL OWNER:	Myrtle Teeter	& KU Endowment Assoc.	
	RR#, St. Address, Box # :	P. O. Box 532	P. O. Box 928	Board of Agriculture, Division of Water Resources
	City, State, ZIP Code :	Johnson, Kansas 67855	Lawrence, Ks. 66044	Application Number: 3,912

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

W

E

N

S

4 DEPTH OF COMPLETED WELL: 375 ft. ELEVATION: 375 ft.

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 260 ft. below land surface measured on mo/day/yr 8/12/98

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 30 in. to 375 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Dewatering
		12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No ☒ X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No ☒ X

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued	Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded	X
		7 Fiberglass		Threaded	

Blank casing diameter **16** in. to **290** ft., Dia. in. to . ft., Dia. in. to . ft.

Casing height above land surface **12** in., weight **42.05** lbs./ft. Wall thickness or gauge No. **.250**

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS:

From	290	ft. to	375	ft., From		ft. to		ft.
From		ft. to		ft., From		ft. to		ft.

GRAVEL PACK INTERVALS:

From	20	ft. to	200	ft., From	260	ft. to	375	ft.
From		ft. to		ft., From		ft. to		ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 20 ft. From 200 ft. to 260 ft. From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? Northwest How many feet? 40' north & 100' west

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/25/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 8/25/98 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Keller

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

Glen Teeter
Stanton County
8/12/98

Location: NW $\frac{1}{4}$ 34-29-40 - From northeast corner of Johnson - 3 miles east to
Western Feedlot Sign, 6 miles south, 770 ft. east
& 80 ft. south to old well (Offset 100 ft. east &
50 ft. south)

Static Water Level - 260'.

Test #3

0' to 1' - Top soil 01
1' to 16' - Brown sandy clay - loose 04
16' to 24' - Brown clay 01
24' to 27' - Brown sandy clay 04
27' to 55' - Brown clay - tight 01
55' to 87' - Brown sandy clay 04
87' to 127' - Brown clay 01
127' to 143' - Fine to medium sand and gravel 17
143' to 152' - Brown clay 01
152' to 162' - Fine to medium sand and gravel 17
162' to 170' - Brown clay 01
170' to 178' - Fine to medium sand and gravel 17
178' to 204' - Brown clay 01
204' to 209' - Fine to medium sand and gravel 17
209' to 212' - Brown clay 01
212' to 241' - Fine to medium sand and gravel - small clay strip 17
241' to 265' - Brown clay - hard pull down 01
265' to 274' - Fine to medium sand and gravel 17
274' to 291' - Brown sandy clay 04
291' to 294' - Fine to medium sand 07
294' to 307' - Fine to medium sand and gravel cemented sand - 10% clay 17
307' to 313' - Brown clay 01
313' to 315' - Fine to medium sand 07
315' to 320' - Brown clay 01
320' to 327' - Fine to medium sand and gravel 17
327' to 332' - Brown clay - gravel streak 01
332' to 338' - Fine to medium sand and gravel
338' to 346' - Fine to medium sand and gravel - tight 17
346' to 366' - Brown sandy clay 04
366' to 372' - Fine to medium sand and gravel 17
372' to 388' - Yellow clay - hard pull down 01
388' to 395' - Red bed - hard pull down 19

RECEIVED

AUG 31 1998

BUREAU OF WATER