

1 LOCATION OF WATER WELL:		Fraction		Section Number	Township Number	Range Number
County: Stanton		NE ¼ NE ¼ SE ¼		35	T 29 S	R 40 E
Distance and direction from nearest town or city street address of well if located within city? From Johnson , appx 6 miles South 5 East				Global Positioning System (decimal degrees, min. of 4 digits)		
2 WATER WELL OWNER: Wylie Martin RR#, St. Address, Box # : 3587 S. Road J City, State, ZIP Code : Johnson City Ks 67855				Latitude: 37.47898		
				Longitude: 101.65384		
				Elevation: 3254		
				Datum: _____		
				Data Collection Method: _____		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 590 ft.				
<div style="text-align: center;"> </div>		Depth(s) Groundwater Encountered 1 _____ ft. 2 _____ ft. 3 _____ ft.				
		WELL'S STATIC WATER LEVEL 318 ft. below land surface measured on mo/day/yr 9/9/08				
		Pump test data: Well water was 383 ft. after 4 hours pumping 1350 gpm				
		Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm				
		WELL WATER TO BE USED AS: 5 _____ 8 Air conditioning 11 Injection well				
		1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				
		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes _____ No x ; If yes, mo/day/yr				
		Sample was submitted _____ Water Well Disinfected? Yes x No _____				
5 TYPE OF CASING USED:		CASING JOINTS: Glued _____ Clamped _____				
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) _____		Welded X				
2 PVC 4 ABS 7 Fiberglass _____		Threaded _____				
Blank casing diameter 16 in. to 590 ft., Dia _____ in. to _____ ft., Dia _____ in. to _____ ft.						
Casing height above land surface 12 in., Weight 42 lbs./ft. Wall thickness or gauge No. .250						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) _____						
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) _____						
SCREEN-PERFORATED INTERVALS: From 397 ft. to 417 ft. From 445 ft. to 585 ft.						
GRAVEL PACK INTERVALS: From 20 ft. to 590 ft. From _____ ft. to _____ ft.						
From _____ ft. to _____ ft. From _____ ft. to _____ ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other _____						
Grout Intervals From 0 ft. to 20 ft. From _____ ft. to _____ ft. From _____ ft. to _____ ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below)						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well						
Direction from well? North West How many feet? 75						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	2	Top soil				
2	9	Sandy Clay				
9	27	Fine Sand				
27	46	Clay few sand				
46	70	Sand fine to med coarse				
70	110	Clay, lime rock, few sand				
110	174	Sand fine to med coarse w/clay, limerock				
174	182	clay				
182	207	Sand fine to med				
207	304	Clay few sand				
304	325	Sand fine thin clay				
325	342	Sticky clay				
342	350	Sand fine small				
350	395	Sticky clay				
395	417	Sand fine to med coarse				
417	445	Sticky clay w/sand				

