

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Stanton	SW 1/4 SW 1/4 SW 1/4	1	T 29 S	R 41 E

Distance and direction from nearest town or city street address of well if located within city?

Johnson: 1S., 1E., N into

2 WATER WELL OWNER: J.M. Huber Corp	#1-1 Richard Arnold
RR#, St. Address, Box # : P.O. Box 2831	Board of Agriculture, Division of Water Resources
City, State, ZIP Code : Borger, Tx 79008	Application Number: 970032

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 420 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 210 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 210 ft. below land surface measured on mo/day/yr 1-23-97 Pump test data: Well water was 399 ft. after 1 hours pumping 60 gpm Est. Yield 60 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to 420 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No..X.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 6 in. to 420 ft., Dia			11 Other (specify)
Casing height above land surface 24 in., weight 2.902 lbs./ft. Wall thickness or gauge No. .280 SDR 21			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	
1 Steel	6 Concrete tile	9 ABS	
2 Brass			
3 Stainless steel	7 Gauzed wrapped	8 Saw cut	11 None (open hole)
4 Galvanized steel	6 Wire wrapped	9 Drilled holes	
SCREEN OR PERFORATION OPENINGS ARE:	7 Torch cut	10 Other (specify)	
1 Continuous slot			
2 Louvered shutter			
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 300 ft. to 420 ft., From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 260 ft. to 420 ft., From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other Hole Plug
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage			
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				
Direction from well? East	How many feet? 120			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	40	Clay			
40	76	Clay / Sandy Clay			
76	100	Sandy Clay			
100	103	Clay			
103	170	Sand			
170	200	Sm. Gravel			
200	206	Sand			
206	299	Clay			
299	416	Sandy Clay / Few Clay Streaks			
416	420	Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-23-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWCL - 430 This Water Well Record was completed on (mo/day/yr) 1-23-97 under the business name of Howard Drlg. Box 806, Beaver, Ok 73932 by (signature) <i>[Signature]</i>
--