			WATER	WELL RECORD	orm WWC-	5 KSA 82a	1212				
l l l l l l l l l l l l l l l l l l l			Fraction		Sec	ction Number	Township Number	Ra	nge Numbe	r	
County: STANTON SW Distance and direction from nearest town or city			SW 1/4	SW 1/4 SE	1/4	4	т 29 8	S R	41 1	EØ)	
					within city?						
		1 mile south		n, Kansas			····				
_	R WELL OW	•									
	Address, Bo	x#: Johnso	n, KS. 67	855			Board of Agricult	ture, Division o	of Water Res	sources	
	e, ZIP Code	<del> </del>	···			1	Application Num				
B LOCAT	E WELL'S L IN SECTION	OCATION WITH	DEPTH OF CO	MPLETED WELL	.397	ft. ELEVA	ΓΙΟΝ:slope			]	
	525110	De De	epth(s) Groundw	ater Encountered 1.	. 260	ft. 2		. ft. 3		ft.	
			ELL'S STATIC V	VATER LEVEL . 2.6.0	ft. b	pelow land surf	ace measured on mo/d	ay/yr .1.2 / 3.	1./.85		
-	NW	NE	Pump test data: Well water was280 ft. after15 hours pumping10 gpm								
	ļ	ı Es	st. Yield . 3.0	Yield . 3.0 gpm: Well water was ft. after hours pumping gpm							
w w	1	E BC	Sore Hole Diameter 9. 3 / 4 in. to								
~	!										
-	SW	SE	1 Domestic								
	!	[ <u>,                                    </u>	2 Irrigation				0 Observation well				
<u>                                     </u>				cteriological sample st	iomitted to D		s; I		-	as sub-	
5 TYPE (	OF BLANK	CASING USED:	tted	5 Wrought iron	0.0		er Well Disinfected? Ye		No		
1 St		3 RMP (SR)		S Asbestos-Cement			CASING JOINTS:				
2 P\		4 ABS					') 	Welded			
				9			ft., Dia				
Casing he	ight above la	and surface.	18ii	ענ טומ ה weight		ابرون. # lhe	t. Wall thickness or gau	III. W		it.	
TYPE OF	SCREEN O	R PERFORATION N	MATERIAL:	, woigilt	7 PV		i. wan mickness or gau		iu i e - 200	, · · · · ·	
1 St		3 Stainless st		5 Fiberglass		_	11 Other (sp				
2 Br	ass	4 Galvanized	steel		9 AB		12 None use				
SCREEN	OR PERFOR	RATION OPENINGS			d wrapped	-		a (open noie) 11 Non	e (open hole	e)	
	ontinuous slo		_				9 Drilled holes		- (	·	
2 Lo	uvered shutt	ter 4 Key	punched	7 Torch	cut		10 Other (specify)				
SCREEN-	PERFORAT	ED INTERVALS:	From257	ft. to	277	ft., Fron	357	ft. to	397	ft.	
			From	ft. to		ft Fron	1	ft to		ft	
(	GRAVEL PA	CK INTERVALS:	From 10	ft. to	397	ft., Fron	1	ft. to		ft.	
			From	ft. to		ft., Fron	1	ft. to		ft.	
_	MATERIAL		nent 2	Cement grout	3 Bento	onite 4	Other	• • • • • • • • • • • • •			
Grout Inte	rvals: From	mY ft.	to ! V	ft., From	ft.		ft., From	ft. to		ft.	
1		ource of possible cor	_	7 50		10 Livest	•	14 Abandoned			
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel s	_	15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit				• •			Fertilizer storage 16 Other (specify below)				
í	atertignt sew from well?	eriines 6 Seepage Nort	•	9 Feedyard			icide storage		• • • • • • • • •	· · · · ·	
FROM	TO TO		LITHOLOGIC LO	OG .	FROM	How man	y 100t:	DLOGIC LOG			
0	2	Surface				<del>  '`</del>	LITTO	LOGIC LOG			
2	40	Clay							<del></del>		
40	80	Fine sand w	/clay stri	ps				***			
80	260	Clay									
260	280	Clay w/medi	um sand st	rips							
280	357	Clay									
357	400	Clay w/medi	um sand st	rips					· · · · · · · · · · · · · · · · · · ·		
					<u> </u>						
		•									
<b></b>											
7 CONTR	RACTOR'S	OR LANDOWNER'S	CERTIFICATION	N: This water well was	(1) constru	cted, (2) recor	nstructed, or (3) plugged	d under my jui	isdiction and	d was	
completed	on (mo/day/	'year) Da	ecember 3.1.	<b>,</b> .1985		and this recor	d is true to the best of n	ny knowledge a	and belief. Ka	ansas	
Water Wel	Contractor's	s License No	164	This Water We	II Record wa	s completed o	n (mo/day/yr)	June.	.10, 1.98	6	
under the	business nar	me of Houck	Bros. Dril	ling Co.		by (signati	ure) Malling Ri	and.			
INSTRUC	TIONS: Use 1	typewriter or ball poir	nt pen, <i>PLEASE</i>	PRESS FIRMLY and	PRINT clear	v. Please fill in	blanks, underline or circ	le the correct a	answers. Ser	nd top	
OWNER a	รร เบ Nansas เกd retain on	Department of Health e for your records.	and Environme	nt, Division of Environn	ent, Environ	mental Geology	y Section, Topeka, KS 66	6620. Send one	to WATER	WELL	
		,									