WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	County	Fraction		Section	number	Township number	Range number	
	Stanton	NE 1/4 NE 1/4NE	1/4	1.	3	т 29 s	R 41	EØ.
Z milos south				ner of well:		Carl Jones		
of the Se corner of Johnson, Ks.				street: tate, zip code:		RFD 2		
4. Locate with "X" in section below: Sketch map:				die, zip code:		Johnson, Ks. 67855 6. Bore hole dia. 912 in. Completion date		
N Sketch indp:						Well depth 450 ft. 5/22/78		
1	<u> </u>				ľ	7 Cable tool X Rotary	Driven Dug	
E - SW SE								
t	l					Mreaded Welded VI	Surface 12	in. lbs./ft.
1 						RMP PVC	th Wall Thickness: in	ches or
5. Type and color of material					τ₀ 2	Dia in. to ft. dept		20
Surface			····	0		10. Screen: Manufacturer's n	ome OWer	
Sandy clay				2	38	Type <u>styrene</u>		
Fine to medium sand w/clay breakers				38	68	Slot/gauze 1/16!! Length 35 Set between 340 ft. and 375 ft.		
Directs seems and lime shalls w/slaw breakers				68	120	ft. a	nd	ft.
Fine to coarse sand, lime shells w/clay breakers Brown clay w/sand strips				120	141	Size runge of malerial		
brown cray	w/ Sand Serips					 Static water level: 260 ft. below land sure 		./day/yr. !/78
Fine to coarse sand w/clay breakers				141	213	12. Pumping level below land surfaces:		
				213	244			
Sandy clay w/embedded sand strips					-	Estimated maximum yield35		
Fine to coarse sand w/small clay breakers				244	265	13. Water sample submitted: mo./day/yr.		
Embedded sand w/clay and lime shells				265	273	Yes X No Date		
				055	774		18 Inches above	grade
Very fine to medium sand and lime shells				273	334	15. Well grouted? _A		
Fine to coarse sand w/clay and lime shells				334	378	With: X Neat cement Bentonite Concrete Depth: From ft. to ft.		
Brwon clay w/fine to coarse sand strips				378	391	16. Nearest source of possible contamination:		
Very fine to coarse sand w/clay breakers				391	406	fr. 135 Direction south Type tail water		
very line to coarse said wy cray breakers						17. Pump:	X Not installed	
Fine to medium sand w/clay breakers				406	421	Manufacturer's name		
Very fine to fine sand & brown clay			421	439		HP Vo		
1017 11110	TO IZIO CANA 4 DIO	y		 		Length of drop pipe Type:	it. capacity	-g.p.m. C
Yellow chalk			439	450	Submersible	Turbine	1 1	
L	(Use a second s	sheet if needed)				Jet Centrifugal	Recipro	ocaring S
18. Elevation:	19. Remarks:			-		20. Water well contractor's o	ertification:	"
						This well was drilled under m	′ '	·
Topography:						is true to the best of my know	reage and belief.	16/5
X Slope						Houck Bros. Dr: Business name Address Box 487, 1	Hiting Co.	ense No.
Slope Upland						Signed M. Beard		6-8/7 5
Valley		· · · · · · · · · · · · · · · · · · ·			<i>)</i>	Signed Authorized rep	resentative Date	<u> </u>