

1 LOCATION OF WATER WELL: County: Stanton Fraction SE 1/4 SW 1/4 SW 1/4 Section Number 14 Township Number T 29 S Range Number R 42 EW

Distance and direction from nearest town or city street address of well if located within city?

Johnson Coop Grain, Manter, Kansas

2 WATER WELL OWNER: Johnson Coop Grain-Manter RR# St Address, Box # : South 160 Highway City, State, ZIP Code : Manter, Kansas Board of Agriculture, Division of Water Resources Application Number: REVISED 3/98

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2-mile square divided into four quadrants (NW, NE, SW, SE) with an 'X' in the SW quadrant.] 4 DEPTH OF COMPLETED WELL: 30 ft ELEVATION: 0 ft. WELL'S STATIC WATER LEVEL: ... ft below land surface measured on mo/day/yr. Pump test data: Well water was NA ft after ... hours pumping ... gpm. Est. Yield NA gpm. Well water was ... ft after ... hours pumping ... gpm. Bore Hole Diameter: 8 in. to 30 ft, and ... in. to ... ft. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below), 2 Irrigation, 4 Industrial, 7 Lawn and garden only, 10 Monitoring well. Was a chemical/bacteriological sample submitted to Department? Yes.....No [checked]; If yes, mo/day/yr sample was submitted. Water Well Disinfected? Yes No [checked]

5 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC [checked], 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole). CASING JOINTS: Glued, Clamped, Welded, Threaded [checked]. Blank casing diameter: .2 in. to 20 ft, Dia. ... in. to ... ft, Dia. ... in. to ... ft. Casing height above land surface: 0 in., weight: Sch 40, lbs./ft. Wall thickness or gauge No. ... TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless steel, 4 Galvanized steel, 5 Fiberglass, 6 Concrete tile, 7 PVC [checked], 8 RMP (SR), 9 ABS, 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot [checked], 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 20 ft to 30 ft, From ... ft to ... ft, From ... ft to ... ft. GRAVEL PACK INTERVALS: From 18 ft to 30 ft, From ... ft to ... ft, From ... ft to ... ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout [checked], 3 Bentonite, 4 Other. Grout Intervals: From 0 ft to 15 ft, From 15 ft to 18 ft, From ... ft to ... ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below) [checked] Unknown. Direction from well? How many feet? 0

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows: 0-2 Clay, Dark Brown; 2-6 Clay, Brown; 6-17 Clay, Light Brown; 17-26 Clay, Red Brown; 26-30 Clay, Red Brown. Additional info: SVE4, Tag #, Flushmount; Project Name: AG-W - Manter; GeoCore # 592, #

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/22/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527. This Water Well Record was completed on (mo/day/yr) 12/30/97 under the business name of GeoCore Services, Inc. by (signature) Dan Roll