AIGHNAY 160 HANTER, KS 67	est town or city street address of 1862- 10' Second of 1	45-TI (3	Johnson Coo	( م.
RR#, St. Address, Box # : 304 HI City, State, ZIP code : JOHNSC	AULAUR AUF		riculture, Division Mumber:	of Water Resources
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL Depth(s) Groundwater Enco			0 ft. 3. 0 f
NV NE	WELL'S STATIC WATER LEVEL Pump testdata: 1	O ft. below land Well water was		on mo/day/yr cours pumping 0 g
; nw ; nL ; i i i	• •	Well water was	0 ft. after 0 h	ours pumping 0 g
<b>W</b>	E Bore Hole Diameter	6.25 in. to 90	ft., and in. t	o 0 ft.
SWX SE	WELL WATER TO BE USED AS: 1	HONITORING		;
2 2F	Was a chemical/bacteriologi			•
YPE OF BLANK CASING USED: PYC lank casing diameter 2 asing height above land surface YPE OF SCREEN OR PERFORATION HAI		THREADED to Oft., Dia	in. to 0	well disinfected? Y
YPE OF BLANK CASING USED: PYC	CASING JOINTS: 1 in. to 90 ft., Dia in. 12 in., weight 0 lbs/ [ERIAL: PVC RE: SAW CUT	THREADED to 0 ft., Dia /ft. Wall thicknes:	in. to 0 s or gauge No.	****
YPE OF BLANK CASING USED: PYC Blank casing diameter 2 Casing height above land surface YPE OF SCREEN OR PERFORATION HAI CREEN OR PERFORATION OPENINGS AF	CASING JOINTS: 1 in. to 90 ft., Dia in. 12 in., weight 0 lbs, [ERIAL: PVC RE: SAW CUT  From 84 ft. to 90 ft., From 0 ft., to 0 ft.,	THREADED to 0 ft., Dia /ft. Wall thickness  , From 0 ft. to , From 0 ft. to , From 0 ft. to	in. to 0 s or gauge Ho. 0 ft. 0 ft. 0 ft.	****
YPE OF BLANK CASING USED: PYC lank casing diameter 2 asing height above land surface YPE OF SCREEN OR PERFORATION HAT CREEN OR PERFORATION OPENINGS AF  CREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  ROUT MATERIAL BENTONITE rout Intervals: From 0 ft. hat is the nearest source of pos	CASING JOINTS: 1 in. to 90 ft., Dia in. 12 in., weight 0 lbs, [ERIAL: PVC RE: SAW CUT  From 84 ft. to 90 ft., From 0 ft. to 0 ft., From 79 ft. to 93 ft.,	THREADED to 0 ft., Dia /ft. Wall thickness  , From 0 ft. to	in. to 0 s or gauge Ho.  Oft. Oft. Oft. Oft. Oft.	ft.
YPE OF BLANK CASING USED: PYC clank casing diameter 2 casing height above land surface yPE OF SCREEN OR PERFORATION MAI CREEN OR PERFORATION OPENINGS AF CREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  ROUT MATERIAL BENTONITE rout Intervals: From 0 ft. hat is the nearest source of pos irection from well?  FROM   TO	CASING JOINTS: 1 in. to 90 ft., Dia in. 12 in., weight 0 lbs, IERIAL: PVC RE: SAW CUT  From 84 ft. to 90 ft., From 0 ft. to 0 ft., From 79 ft. to 93 ft., From 0 ft. to 0 ft., Sible contamination: FUEL STORAGE	THREADED to 0 ft., Dia /ft. Wall thickness  , From 0 ft. to	in. to 0 s or gauge Ho.  Oft. Oft. Oft. Oft. Oft. Oft.	ft.
YPE OF BLANK CASING USED: PYC Plank casing diameter 2 PROPERTORATION OPENINGS AFTER OF PERFORATION OPENINGS AFTER OF PERFORATION OPENINGS AFTER OF PERFORATED INTERVALS:    CREEN PERFORATED INTERVALS:   CREEN PERFORATED INTERVALS:   CREEN PERFORATED INTERVALS:   CREEN PERFORATED INTERVALS:   CREEN PERFORATED INTERVALS:   PROPERTORATED INTERVALS:   PROPERTORATION OPENINGS AFTER OPENINGS	CASING JOINTS: 1 in. to 90 ft., Dia in. 12 in., weight 0 lbs/ IERIAL: PVC RE: SAW CUT  From 84 ft. to 90 ft., From 9 ft. to 0 ft., From 79 ft. to 93 ft., From 0 ft. to 0 ft., Sible contamination: FUEL STORAGE LITHOLOGIC LOG / ROCK 09 GRAVEL	THREADED to 0 ft., Dia /ft. Wall thickness  , From 0 ft. to	in. to 0 s or gauge Ho.  Oft. Oft. Oft. Oft. Oft. Oft.	ft.  How many feet?
YPE OF BLANK CASING USED: PYC clank casing diameter 2 casing height above land surface type of Screen or Perforation Mai creen or Perforation openings af creen Perforated intervals:  GRAVEL PACK INTERVALS:  ROUT MATERIAL BENTONITE rout Intervals: From 8 ft. hat is the nearest source of pos irection from well?  FROM   TO   0	CASING JOINTS: 1 in. to 90 ft., Dia in. 12 in., weight 0 lbs/ IERIAL: PVC RE: SAW CUT  From 84 ft. to 90 ft., From 9 ft. to 0 ft., From 79 ft. to 93 ft., From 0 ft. to 0 ft.,  to 79 ft., From 0 ft. to esible contamination: FUEL STORAGE  LITHOLOGIC LOG / ROCK 09 GRAYEL	THREADED to 0 ft., Dia /ft. Wall thickness  , From 0 ft. to	in. to 0 s or gauge Ho.  Oft. Oft. Oft. Oft. Oft. Oft.	ft.  How many feet?
TYPE OF BLANK CASING USED: PYC Blank casing diameter 2 casing height above land surface TYPE OF SCREEN OR PERFORATION HAI CREEN OR PERFORATION OPENINGS AF CREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL BENTONITE Grout Intervals: From 8 ft. Hat is the nearest source of postirection from well?  FROM   TO   0	CASING JOINTS: 1 in. to 90 ft., Dia in. 12 in., weight 0 lbs, IERIAL: PVC RE: SAW CUT  From 84 ft. to 90 ft., From 0 ft. to 0 ft., From 79 ft. to 93 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft., Ato 79 ft., From 0 ft. to 0 sible contamination: FUEL STORAGE LITHOLOGIC LOG V ROCK 09 GRAVEL  NLACHIE 19 LAYERS 05 CLAY 35 CALACHIE	THREADED to 0 ft., Dia /ft. Wall thickness  , From 0 ft. to	in. to 0 s or gauge Ho.  Oft. Oft. Oft. Oft. Oft. Oft.	ft.  How many feet?
IYPE OF BLANK CASING USED: PYC Blank casing diameter 2 Casing height above land surface IYPE OF SCREEN OR PERFORATION HAI ECREEN OR PERFORATION OPENINGS AF CICREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL BENTONITE Grout Intervals: From 8 ft. Hat is the nearest source of postirection from well?  FROM   TO    0	CASING JOINTS: 1 in. to 90 ft., Dia in. 12 in., weight 0 lbs, IERIAL: PVC RE: SAW CUT  From 84 ft. to 90 ft., From 0 ft. to 0 ft., From 79 ft. to 93 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft., Ato 79 ft., From 0 ft. to 0 sible contamination: FUEL STORAGE LITHOLOGIC LOG V ROCK 09 GRAVEL  NLACHIE 19 LAYERS 05 CLAY 35 CALACHIE	THREADED to 0 ft., Dia /ft. Wall thickness  , From 0 ft. to	in. to 0 s or gauge Ho.  Oft. Oft. Oft. Oft. Oft. Oft.	ft.  How many feet?
TYPE OF BLANK CASING USED: PYC Blank casing diameter 2 casing height above land surface TYPE OF SCREEN OR PERFORATION HAI CREEN OR PERFORATION OPENINGS AF CREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL BENTONITE Grout Intervals: From 8 ft. Hat is the nearest source of postirection from well?  FROM   TO   0	CASING JOINTS: 1 in. to 90 ft., Dia in. 12 in., weight 0 lbs, IERIAL: PVC RE: SAW CUT  From 84 ft. to 90 ft., From 0 ft. to 0 ft., From 79 ft. to 93 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft., Ato 79 ft., From 0 ft. to 0 sible contamination: FUEL STORAGE LITHOLOGIC LOG V ROCK 09 GRAVEL  NLACHIE 19 LAYERS 05 CLAY 35 CALACHIE	THREADED to 0 ft., Dia /ft. Wall thickness  , From 0 ft. to	in. to 0 s or gauge Ho.  Oft. Oft. Oft. Oft. Oft. Oft.	ft.  How many feet?