WATER WELL RECORD Form WWC-5 KSA 82a-1212

| Distance and direction from neare JOHNSON COOP - S. OF EASTERNHOST | BIN IN ELEVATOR | | | |
|--|--|---|---|-------------------------------------|
| WATER WELL OWNER: SKYLAM RR#, St. Address, Box # : 304 HI City, State, ZIP code : JOHNSO | D GRAIN, LLC. ペゴール GHLAND AYE. N, KS 67855- | | • | on of Water Resources |
| LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: | 4 DEPTH OF COMPLETED WEL Depth(s) Groundwater E | | | 0 ft. 3. 0 |
| \ | WELL'S STATIC WATER LEVE Pump testdata: | L Oft. below land Well water was | | d on mo/day/yr D hours pumping 0 |
| , | Estimated Yield 0 gp | m: Well water was | O ft. after O | hours pumping 0 |
| | E Bore Hole Diameter | 6.25 in. to 90 f | t., and in. | to 0 ft. |
| | WELL WATER TO BE USED AS | : NONITORING | | } |
| SW SE | Was a chemical/bacteriol | | | No; ter well disinfected? |
| TYPE OF BLANK CASING USED: PVC Blank casing diameter 2 Casing height above land surface TYPE OF SCREEN OR PERFORATION MAT SCREEN OR PERFORATION OPENINGS AR | CASING JOINTS in. to 90 ft., Dia i 12 in., weight 0 l ERIAL: PVC E: SAW CUT | : THREADED n. to 0 ft., Dia bs/ft. Wall thickness | in. to or gauge No. | 0 ft. |
| TYPE OF BLANK CASING USED: PVC Blank casing diameter 2 Casing height above land surface TYPE OF SCREEN OR PERFORATION MAT SCREEN OR PERFORATION OPENINGS AR SCREEN PERFORATED INTERVALS: GRAYEL PACK INTERVALS: | CASING JOINTS in. to 90 ft., Dia i 12 in., weight 0 li ERIAL: PVC E: SAW CUT From 84 ft. to 90 f From 0 ft. to 0 f From 77 ft. to 93 f | : THREADED in. to 0 ft., Dia bs/ft. Wall thickness it., From 0 ft. to | in. to or gauge No. Oft. Oft. Oft. | |
| TYPE OF BLANK CASING USED: PVC Blank casing diameter 2 Casing height above land surface TYPE OF SCREEN OR PERFORATION NAT SCREEN OR PERFORATION OPENINGS AR SCREEN PERFORATED INTERVALS: GRAYEL PACK INTERVALS: | CASING JOINTS in. to 90 ft., Dia i 12 in., weight 0 li ERIAL: PVC E: SAW CUT From 84 ft. to 90 f From 0 ft. to 0 f From 77 ft. to 93 f From 0 ft. to 0 f | t., From 0 ft. to | in. to or gauge No. Oft. Oft. Oft. Oft. | |
| IYPE OF BLANK CASING USED: PVC Blank casing diameter 2 Casing height above land surface IYPE OF SCREEN OR PERFORATION OPENINGS AR BCREEN OR PERFORATED INTERVALS: GRAYEL PACK INTERVALS: GROUT HATERIAL BENTONITE Brout Intervals: From 0 ft. What is the nearest source of positive time of the series of the serie | CASING JOINTS in. to 90 ft., Dia i 12 in., weight 0 li ERIAL: PVC E: SAW CUT From 84 ft. to 90 f From 0 ft. to 0 f From 77 ft. to 93 f From 0 ft. to 0 f LITHOLOGIC LOG ROCK 09 GRAVEL LACHIE 19 LAYERS | t., From 0 ft. to | in. to or gauge No. Oft. Oft. Oft. Oft. Oft. | 0 ft. |
| ITYPE OF BLANK CASING USED: PVC Blank casing diameter 2 Casing height above land surface ITYPE OF SCREEN OR PERFORATION OPENINGS AR BCREEN OR PERFORATED INTERVALS: GRAYEL PACK INTERVALS: GRAYEL PACK INTERVALS: GROUT HATERIAL BENTOMITE Brout Intervals: From 0 ft. What is the nearest source of positive time of the source of positive time of the source of positive time of the source of time of | CASING JOINTS in. to 90 ft., Dia i 12 in., weight 0 li ERIAL: PVC E: SAW CUT From 84 ft. to 90 f From 0 ft. to 0 f From 77 ft. to 93 f From 0 ft. to 0 f LITHOLOGIC LOG ROCK 09 GRAVEL LACHIE 19 LAYERS DS CLAY 35 CALACHIE DS CLAY 06 SHALL GRAVEL | t., From 0 ft. to | in. to or gauge No. Oft. Oft. Oft. Oft. Oft. | ft. How many feet? |
| TYPE OF BLANK CASING USED: PVC Blank casing diameter 2 Casing height above land surface TYPE OF SCREEN OR PERFORATION OPENINGS AR SCREEN OR PERFORATED INTERVALS: GRAYEL PACK INTERVALS: GROUT MATERIAL BENTOMITE Grout Intervals: From 0 ft. What is the nearest source of positive to the performance of | CASING JOINTS in. to 90 ft., Dia i 12 in., weight 0 li ERIAL: PVC E: SAW CUT From 84 ft. to 90 f From 0 ft. to 0 f From 77 ft. to 93 f From 0 ft. to 0 f LITHOLOGIC LOG ROCK 09 GRAVEL LACHIE 19 LAYERS DS CLAY 35 CALACHIE DS CLAY 06 SHALL GRAVEL | t., From 0 ft. to | in. to or gauge No. Oft. Oft. Oft. Oft. Oft. | ft. How many feet? |