


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: KINGMAN		SE 1/4 SE 1/4 NE 1/4	13	T 29 S	R 5 W E/W
Distance and direction from nearest town or city street address of well if located within city? 6 1/2 S. of MacArthur Rd. on Cheney Reservoir Rd., W. side of Rd., Norwich, Ks.					
2 WATER WELL OWNER:		John Fearey			
RR#, St. Address, Box # :		R.R. 1			
City, State, ZIP Code :		Norwich, Ks.			
Board of Agriculture, Division of Water Resources		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 60 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 8-19-81 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded			
2 PVC 4 ABS		7 Fiberglass Threaded			
Blank casing diameter 5 in. to 20 ft. Dia		Cer-Mac Styrene SDR-26 in. to ft.			
Casing height above land surface 12 in. weight 1.59 lbs./ft.		Wall thickness or gauge No. 203			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut .06 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		7 Torch cut 10 Other (specify)			
2 Louvered shutter 4 Key punched					
SCREEN-PERFORATED INTERVALS: From 20 ft. to 80 ft.		From ft. to ft.			
GRAVEL PACK INTERVALS: From 14 ft. to 80 ft.		From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 40" ft. to 14 ft. From ft. to ft. From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		How many feet? 75			
Direction from well? Northeast					
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0 3 Sandy Topsoil					
3 7 Brown Clay					
7 80 Red Shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-19-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 10-26-81 under the business name of Harp Well & Pump Serv., Inc. by (signature) M. Arnold					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					