

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: KINGMAN	SW 1/4 SW 1/4 SE 1/4	4	T 29 S	R 6 SW

Distance and direction from nearest town or city street address of well if located within city?
2 Miles North 1/2 Mile East Of Belmont, Kans.

2 WATER WELL OWNER: Larry Ward	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : 7544 SE 70TH	Application Number:
City, State, ZIP Code : Kingman, Kans. 67068	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 35' ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 14' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 14' ft. below land surface measured on mo/day/yr Jan. 5-96 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 12 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 7/8 in. to 35' ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well XX1 Domestic x3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
XX2 PVC	7 Fiberglass		Threaded
Blank casing diameter 5 in. to 24' ft. Dia			
Casing height above land surface 20' in. weight 160 lbs./ft. Wall thickness or gauge No. SDR 26			
TYPE OF SCREEN OR PERFORATION MATERIAL:	XX PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	XX Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 35' ft. to 24' ft.		
GRAVEL PACK INTERVALS:	From 35' ft. to 21' ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	XX Bentonite	4 Other
Grout Intervals:	From 21' ft. to 0' ft.			
What is the nearest source of possible contamination:	XX10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? North			How many feet? App: 50'	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	3'	Top Soil.			
3'	7'	Clay			
7'	18'	Fine Sand.			
18'	32'	Medium Course Sand.			
32'	35'	Course and fine Gravel			
35'		Red Bed.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Jan 3 - 1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 112 This Water Well Record was completed on (mo/day/yr) Jan. 23 - 1996 under the business name of Wells Drilling Co. by (signature) Dal Wells
--