

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Kingman		NW 1/4 NW 1/4 NE 1/4	29	T 29 S	R 6 W E/W
Distance and direction from nearest town or city street address of well if located within city? 1 1/2 S 37 1/4 W of Belmont					
2 WATER WELL OWNER: Carl Durr			Board of Agriculture, Division of Water Resources		
RR#, St. Address, Box #: 1380 N Boardwalk Rd			Application Number:		
City, State, ZIP Code: Milton, Ka. 67106					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 67.31 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 31 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 31 ft. below land surface measured on mo/day/yr 11-06-97			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 10 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 67 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: <u>Glued</u> Clamped			
1 Steel		5 Wrought iron			
2 PVC		6 Asbestos-Cement			
3 RMP (SR)		7 Fiberglass			
4 ABS		8 Concrete tile			
		9 Other (specify below)			
Blank casing diameter 5 in. to 58 ft. Dia		Casing height above land surface 17 in., weight lbs./ft. Wall thickness or gauge No. 210			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC			
1 Steel		8 RMP (SR)			
2 Brass		9 ABS			
3 Stainless steel		10 Asbestos-cement			
4 Galvanized steel		11 Other (specify)			
5 Fiberglass		12 None used (open hole)			
6 Concrete tile					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped			
1 Continuous slot		6 Wire wrapped			
2 Louvered shutter		7 Torch cut			
3 Mill slot		8 Saw cut			
4 Key punched		9 Drilled holes			
5 Other (specify)		10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		11 None (open hole)			
From 58 ft. to 65 ft.					
From ft. to ft.					
GRAVEL PACK INTERVALS:					
From 23 ft. to 67 ft.					
From ft. to ft.					
6 GROUT MATERIAL:		3 Bentonite			
1 Neat cement		4 Other			
2 Cement grout					
Grout Intervals: From 3 ft. to 23 ft.		From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens			
1 Septic tank		11 Fuel storage			
2 Sewer lines		12 Fertilizer storage			
3 Watertight sewer lines		13 Insecticide storage			
4 Lateral lines		14 Abandoned water well			
5 Cess pool		15 Oil well/Gas well			
6 Seepage pit		16 Other (specify below)			
7 Pit privy					
8 Sewage lagoon					
9 Feedyard					
Direction from well? None with in 500 Ft.		How many feet? 500			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	soil			
2	6	clay			
6	22	fine sand			
22	27	clay			
27	35	fine sand			
35	37	sand			
37	41	fine sand			
41	54	sand			
54	58	clay			
58	65	sand some medium			
65	67	red shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-06-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 140 This Water Well Record was completed on (mo/day/yr) 11-20-97 under the business name of Lynam Inc. by (signature) <i>Dean Kynman</i>					