

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Kingman	Fraction 1/4 NW 1/4 NW 1/4	Section number 31	Township number T 29 S R 6	Range number 6	X W
2. Distance and direction from nearest town or city: 3 Mi. East & 1-3/4 Mi. N. of Rago, Kansas Street address of well location if in city:				3. Owner of well: Gene Millard R.R. or street: Rago, Kansas 67128 City, state, zip code:			
4. Locate with "X" in section below: N W E S 1 Mile 1 Mile		Sketch map: Well No. 1 (TH 2-77)		6. Bore hole dia. 30 in. Completion date 4/26/77 Well depth 70 ft.			
5. Type and color of material		From	To	7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary			
Soil		0	2	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other			
Brown clay		2	10	9. Casing: Material steel Height: Above or xxx Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 18 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 31.75 lbs./ft. Dia. 16 in. to 38 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 0.188 "			
Fine to med. sand		10	19	10. Screen: Manufacturer's name Doerr Metal Products Type Steel Dia. 16 " Slot/gauze 1/8 " Length 32 ' Set between 38 ft. and 70 ft. ft. and <input type="checkbox"/> ft. Gravel pack? yes Size range of material 1/8 X 1/4			
Brown clay		19	22	11. Static water level: 7.58 ft. below land surface Date 4/29/77 mo./day/yr.			
Med. to coarse sand & gravel		22	50	12. Pumping level below land surfaces: 5.64 ft. after 4 hrs. pumping 700 g.p.m. ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 700 g.p.m.			
Fine sand		50	53	13. Water sample submitted: mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date			
Med. to coarse sand & gravel		53	70	14. Well head completion: <input type="checkbox"/> Pitless adapter 18 Inches above grade			
Red shale		70		15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.			
				16. Nearest source of possible contamination: ft. 1350 Direction SSW Type Farm Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No			
				17. Pump: Manufacturer's name Layne & Bowler Not installed Model number 12" KML HP 60 Volts <input type="checkbox"/> Length of drop pipe 60 ft. capacity 700 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other			
				20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne Western Co., Inc. License No. 102 Business name Wichita, Kansas Address 1111 1/2 Signed 5/13/77 Date 5/13/77 Authorized representative			
18. Elevation:		19. Remarks:					
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input checked="" type="checkbox"/> Valley							