WATER W	FII PE	COPD	Form W	WC-5	Division of Wate	r Resources App. N	48,364	
			Fraction	VY.C.F.S	Section Number		Range Num	her
		MAN ORD		1/4 SW 1/4	24	T 29 S		E ØW
Street/Rui	ral Address o	of Well Location: i	f unknown, distance d	& direction	Global Positioning			
from near	est town or i	ntersection: If at o	Latitude: . 37.503	34.1	(in decima			
SE 100th St. and SE 100th Ave					Longitude: -97.92697 (in decimal degrees)			
					Elevation:			
2 WATER WELL OWNER: Kenton Rosenhagen					Datum: ☐ WGS 84, ☐ NAD 83, ☑ NAD 27			
2 WATER WELL OWNER: Kenton Rosenhagen RR#, Street Address, Box #: 12236 SE 110th					Collection Method:			
City, State, ZIP Code : Norwich, KS 67118					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
		INOLWICH	, NO OF FIG.	Est. Accuracy:	<3 m, 🔲 3-5 m, 🔲	5-15 m, □ >	15 m	
3 LOCATE WELL								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 86 ft. SECTION BOX: Depth(s) Groundwater Encountered (1) 12 ft (2) ft (3) ft.								
SECTION BOX: Depth(s) Groundwater Encountered (1).12 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr								
Pump test data: Well water wasft. after hours pumping								
EST. YIELD 3.0 gpm. Well water was								
W E Bore Hole Diameter 30 in. to 86 ft., and in. to								
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
Was a chemical/bacteriological sample submitted to Department? Yes No								
S If yes, mo/day/yr sample was submitted								
water well disinfected? La Yes No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: V Glued Clamped Welded Threaded								
Casing diameter .16 in to								
Casing height above land surface12								
Steel ☐ Stainless Steel ✓ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)								
Louvered shutter								
From ft. to ft. From ft. to ft.								
GRAVEL PACK INTERVALS: From 20 ft. to 86 ft., From ft. to ft.								
From								
0 GROUT MATERIAL: Neat cement Cement grout 7 Rentonite 10 Other								
Grout intervals: From .9								
what is the hearest source of possible contamination:								
	ic tank er lines	Lateral line Cesspool		ens				
☐ Wate	ertight sewer l	ines	t Feedvard	☐ Fuel storage ☐ Fertilizer sto			-open field	
Direction	from well		<u></u>	Distance f	rom well			**********
FROM TO)	LITHOLOGI	CLOG	FROM		OG (cont.) <u>or</u> PLU		ERVALS
0' 3'	Topsoi							
3' 40'	Clay							**************************************
40' 50' 50' 70'	Fine Sa	and with Clay						
50' 70' 70' 85'	Fine Sa							
		Medium Sand						
128 85	Silale							
							~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	
						-,		
						· · · · · · · · · · · · · · · · · · ·		*****
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .09/23/2013 and this record is true to the best of my knowledge and belief.								
Railsas water well Contractor's License No238 This Water Well Record was completed on (mo/day/year) 209/26/2013								
under the bus	iness name (of Premier Pum	lp & Well Service In	C	by (signature)	$(U \land \land$	SIN NOW	
INSTRUCTION	VS : Use typev	vriter or ball point pen.	PLEASE PRESS FIRMLY	and PRINT cles	arly Please fill in blanks	and check the correct	answers Send o	ne copy to
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
<u>Le civiliano.</u>	<u> </u>		http://www.kdheks.gov			5.00 TOL CACH CONSULCT	ou won, visit us	. a.