

1 LOCATION OF WATER WELL: County: Kingman, Kns.		Fraction se 1/4 nw 1/4 nw 1/4		Section Number 25		Township Number T 29 S		Range Number R 7																																																	
Distance and direction from nearest town or city street address of well if located within city? 9 miles so 2 1/2 miles east of Kingman, Kns.																																																									
2 WATER WELL OWNER: Ted Maple RR#, St. Address, Box # : RT# 1 City, State, ZIP Code : Ulysses, Kns. 67880																																																									
Board of Agriculture, Division of Water Resources Application Number:																																																									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 61' Dec 30-89 ft. ELEVATION: 21' ft.																																																						
			Depth(s) Groundwater Encountered 1. 21' ft. 2. 21' ft. 3. 21' ft. WELL'S STATIC WATER LEVEL 21' ft. below land surface measured on mo/day/yr Dec 30-89 Pump test data: Well water was NA ft. after NA hours pumping NA gpm Est. Yield NA gpm: Well water was NA ft. after NA hours pumping NA gpm Bore Hole Diameter 8 1/4" in. to 5 1/2' ft., and 61' in. to 61' ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes XX No XX If yes, mo/day/yr sample was submitted Dec 30-89 Water Well Disinfected? Yes XX No XX																																																						
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped XX 2 PV XX 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded XX Blank casing diameter 5" in. to 50" ft., Dia 50" in. to 50" ft., Dia 50" in. to 50" ft. Casing height above land surface 17" in., weight 160 lbs./ft. Wall thickness or gauge No. Sdr 26 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) XX 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped XX Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) XX SCREEN-PERFORATED INTERVALS: From 61' ft. to 50' ft., From 50' ft. to 50' ft. GRAVEL PACK INTERVALS: From 61' ft. to 17' ft., From 17' ft. to 17' ft.																																																									
6 GROUT MATERIAL: 1 Neat cement XX 2 Cement grout 3 Bentonite 4 Other XX Grout Intervals: From 17' ft. to 6' ft., From 6' ft. to 6' ft., From 6' ft. to 6' ft. What is the nearest source of possible contamination: XX 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? East How many feet? 500'																																																									
<table border="1"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0'</td><td>6'</td><td>Sandy top soil</td><td></td><td></td><td></td></tr><tr><td>6'</td><td>18'</td><td>Clay.</td><td></td><td></td><td></td></tr><tr><td>18'</td><td>23'</td><td>Brn clay.</td><td></td><td></td><td></td></tr><tr><td>23'</td><td>36'</td><td>Fine sand.</td><td></td><td></td><td></td></tr><tr><td>36'</td><td>49'</td><td>Brn clay.</td><td></td><td></td><td></td></tr><tr><td>49'</td><td>61'</td><td>Course sand.</td><td></td><td></td><td></td></tr><tr><td></td><td></td><td>Red bed.</td><td></td><td></td><td></td></tr></tbody></table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0'	6'	Sandy top soil				6'	18'	Clay.				18'	23'	Brn clay.				23'	36'	Fine sand.				36'	49'	Brn clay.				49'	61'	Course sand.						Red bed.			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																				
0'	6'	Sandy top soil																																																							
6'	18'	Clay.																																																							
18'	23'	Brn clay.																																																							
23'	36'	Fine sand.																																																							
36'	49'	Brn clay.																																																							
49'	61'	Course sand.																																																							
		Red bed.																																																							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Dec 30 -89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 112 This Water Well Record was completed on (mo/day/yr) Mar. 23 -90 under the business name of Wells Drilling Co. by (signature) Dal Wells																																																									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																									