

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Kingman		NW ¼ NW ¼ NE ¼		27		T 29 S		R 9 EW	
Distance and direction from nearest town or city street address of well if located within city? 4 Miles North, ½ West Of ZENDA, KNS.									
2 WATER WELL OWNER:		S.J. Goetz RR#, St. Address, Box # : 10060 SW 90th Ave City, State, ZIP Code : Spivey, Kans. 67142							
		Board of Agriculture, Division of Water Resources Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 36' ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1 20' ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 19' ft. below land surface measured on mo/day/yr Aug. 2- 1996							
		Pump test data: Well water was ft. after hours pumping gpm Est. Yield 15 gpm: Well water was NA ft. after hours pumping gpm Bore Hole Diameter 7 7/8" in. to 36' ft., and in. to ft.							
		WELL WATER TO BE USED AS: ☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes. ☒ No. ☒ If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes ☒ No							
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded ☒ 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 5" in. to 19' ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 16" xxxx in., weight 2.28 lbs./ft. Wall thickness or gauge No. SDR 26							
TYPE OF SCREEN OR PERFORATION MATERIAL:		☒ 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped ☒ Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS:		From 19' ft. to 36' ft., From ft. to ft. From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS:		From 36' ft. to 19' ft., From ft. to ft. From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout ☒ 3 Bentonite 4 Other Grout Intervals: From 19' ft. to 1' ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit ☒ 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? East How many feet? 150'							
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0'	4'	Top Soil.							
4'	20'	Brown Clay.							
20'	22'	Fine Sand.							
22'	27'	White Clay.							
27'	30'	Medium Course Sand.							
30'	36'	Red Bed.							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Aug. 2 1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 112 This Water Well Record was completed on (mo/day/yr) Aug. 19 - 1996 under the business name of Wells Drilling Co. by (signature) <i>Dal Wells</i>									