

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Kingman	SE 1/4 SW 1/4 NW 1/4	29	T 29 S	R 9 E/W

Distance and direction from nearest town or city street address of well if located within city?

2 Miles West 1 1/4 South Of Willodale, Kans.

2 WATER WELL OWNER: Peggy Goetz	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: Box 122	Application Number:
City, State, ZIP Code: Garden Plain, Kansas 67050	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 65' ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 19' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 18' ft. below land surface measured on mo/day/yr Aug. 6 -94 Pump test data: Well water was NA ft. after hours pumping gpm Est. Yield NA gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 7/8" in. to 65' ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued XX Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
XX PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5" in. to 53' ft., Dia			Threaded
Casing height above land surface 16" in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26			
TYPE OF SCREEN OR PERFORATION MATERIAL:	XX 7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	XX 8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 65' ft. to 53' ft.	From ft. to ft.	From ft. to ft.
GRAVEL PACK INTERVALS:	From 65' ft. to 47' ft.	From 41' ft. to 22' ft.	From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	XX 3 Bentonite	4 Other
Grout Intervals:	From 47' ft. to 41' ft.	From 22' ft. to 2' ft.	From ft. to ft.	From ft. to ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	XX 15 Oil well/Gas well
				12 Fertilizer storage
				16 Other (specify below)
				13 Insecticide storage
Direction from well? South East				How many feet? App. 1320'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	4'	Heavy Top Soil.			
4'	11'	Clay.			
11'	19'	Sandy Clay.			
19'	29'	Fine Sand.			
29'	37'	White Clay.			
37'	46'	Medium Fine Sand.			
46'	48'	Clay.			
48'	65'	Course Sand & Fine Gravel.			
65'		Red Bed.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Aug 5 -94 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 112 This Water Well Record was completed on (mo/day/yr) Sept 2 -94
under the business name of Wells Drilling Co. by (signature) <i>Ral Wells</i>