163 WATER		Well #1 RECORD	Form WWC-	5	Division of W	/ater Resources; App. No	44,633
1 LOCA	TION OF	WATER WELL:		NIE 1/4	Section Numb		er Range Number
	y: Phillip ce and direct		NW 1/4 NW 1/4		8 Global Positio	T 2 S	R 19 E W degrees, min. of 4 digits)
within	city? App	roximately 3 1/2 miles	south and 2 1/4 miles e	ast	Latitude: 3	9.899488	
	ng Island	OWNER: Phillips Co	unty Rural Water Distric	st #1	Longitude: -99.487121 Elevation: Unknown		
RR#,	St. Addres	ss, Box # : 276 W. Sta	ate Street		Datum: NA		
City,	State, ZIP	Code : Phillipsbur	g, KS 67661			ion Method: WAAS C	3PS Unit
	TE WEL	L'S 4 DEPTH OF CO	MPLETED WELL	15	57	ft.	
	ATION I AN ''X''						3)ft,
WITH AN "X" IN SECTION BOX: N Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) WELL'S STATIC WATER LEVEL 120 ft. below land surface measured on mo/day/yr Pump test data: Well water was Not checked ft. after hours pumping g							
	N Iv I	Pump tes	t data: Well water was gpm: Well water was	ot checke	ft after	hours pumpin	gg gpm
NW	/NE	WELL WATED	TO BE USED AS: (5) Pu				
w L	NE	I I	3 Feedlot 6 Oil fie				
			4 Industrial 7 Dome				, , ,
SW	SE	Was a chemical/b	acteriological sample sub	mitted to	Department?	Yes No 🗸	. If yes, mo/day/yrs
	S	Sample was subm	itted	Water	well disinfect	ed? Yes 🗸 No	
5 TYP	E OF CAS		ought Iron 8 Cor				✓ Clamped
		RMP (SR) 6 Ast	estos-Cement 9 Oth	er (speci	fy below)	Welde	d
2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 8 in. to 135 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 24 in., weight 8.25 lbs./ft. Wall thickness or gauge No500							
Casing height above land surface 24 in., weight 8.25 lbs./ft. Wall thickness or gauge No							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
	Brass	3) Stainless Steel 5	Concrete tile 8 RM (SR) 10	ABS Ashestos-Cem	nent 12 None used (one	en hole)
SCREEN	OR PERI	FORATION OPENINGS	ARE:				
	Continuou	s slot 3 Mill slot	5 Gauzed wrapped 7	Torch cut	9 Drilled	holes 11 None (open	hole)
SCREEN	: Louvered N-PERFOR	RATED INTERVALS: F	6 Wire wrapped 8	15	55 ft Fro	m ft. to	o ft.
Corassi		F	rom ft. to		ft., Fro	m ft. te	o ft.
	GRAVEL	PACK INTERVALS: F	rom 135 ft. to rom ft. to rom 120 ft. to rom 27 ft. to	15	6 ft., Fro	m fit to	o ft.
6 CPOI	TMATE	DIAL 1 Next Coment	Cement grout 3 Be	10	O II., Fro	m II. II	o II. oleplug
0 GROC	Comp	acted Soil	6 27	ntonite (4)Other	100-1	20
What is t	itervals: he nearest s	From 0-0 ft. to ource of possible contamination	6-27 ft., From		. ft. to	ft., From	20 ft. to
1 Seption 2 Sewe	c tank	4 Lateral lines 5 Cess pool	7 Pit privy	0 Livesto 1 Fuel sto	ock pens 13	Insecticide Storage Abandoned water well	(16) Other (specify below)
	rtight sewer	~ '			0	Oil well/gas well	None known
Direction	from wel	1?		How man	ny feet?		
FROM	TO	LITHOLOGI	C LOG	FROM	TO TO	PLUGGING IN	NTERVALS
0 4	21	Topsoil, clay Clay, brown					
21	36	Cemented sand	-				
36	40	Clay, gray and brown					
40 95	95 127	Clay, gray and brown		-			
127	154	Sand and gravel, fine					
154	156	Clay, gray					
				+			
		R'S OR LANDOWNER'S	S CERTIFICATION:	This water	well was (1)	constructed (2) recontrue to the best of my kno	istructed (3) plugged
under my Kansas V	y jurisdiction Vater Well (n and was completed on (me Contractor's License No.				true to the best of my kno ted on (mo/day/yearn)	
Under the	e business n	ame of Clarke Well & E	quipment, Inc.	by	(signature)	merch Clark	· · · · · · · · · · · · · · · · · · ·
INSTRUC	TIONS: Use	typewriter or ball point pen. P	LEASE PRESS FIRMLY and PRINT ent, Bureau of Water, Geology Se	clearly. Pl	lease fill in blanks,	underline or circle the correct Suite 420. Topeka Kansas 6	ct answers. Send top three 6612-1367. Telephone
785-296-5	522. Send or	ne to WATER WELL OWNER	and retain one for your records.	Fee of \$5.0	00 for each constru	icted well.	

8576

Well #1