CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

Location listed as:	County: Nor Ton Location changed to:
Section-Township-Range: 8-2 5-21 W	8-25-21 W
Fraction (1/4 1/4 1/4): None Given	SW NW SE
Other changes: Initial statements:	
Changed to:	
Comments:	
verification method: Written description,	city street map,
verification method: Written description, and mapping tool on KGS w	ebsite.
	initials: DR date: 10/2/2006

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

1.	MATER MELL DEC	ODD Form WWO 5	KSA 82a-	1010 ID No				
1 LOCATION OF WATER WELL:	VATER WELL REC Fraction	ORD Form WWC-5		1212 ID No tion_Number	Township	Number	Range Nu	ımher
		1/		Kumber	T 2		1	
County: Norton	1/4		1/4			. S	R 2/	,£ /W
Distance and direction from nearest	•	~ <i>II</i> .	, ,	-1				
In Almenak	5	100 lan	Horn	37.				
2 WATER WELL OWNER:	of Callai	way	•					
RR#, St. Address, Box # : 700					Board of	Aariculture. [Division of Water	Resources
	nena.ks					n Number:		
3 LOCATE WELL'S LOCATION WIT		OMPLETED WELL	lala	ft. ELEVAT	ION:			
AN "X" IN SECTION BOX:	1 11	dwater Encountered						
N N	WELL'S STATIC	C WATER LEVEL 26.	for ft held	land surface	a measured on r	no/day/yr)	
		np test data: Well water						
1 1		gpm: Well water						
NW NE	I		Public water		8 Air conditioni		njection well	31
	_1 Domestic				9 Dewatering		Other (Specify bel	
W E	2 Irrigation	4 Industrial 7	Domestic (lav	vn & garden)	10 Monitoring w	ell		
swse	Was a chemica	l/bacteriological sample	submitted to	Department? V	es No L	· If yes n	no/day/yre sample	a was sub-
	mitted	i/bacteriological sample	Submitted to	•	ater Well Disinfe			lo
	Tillite G			***	tor Well District			
S								
TYPE OF BLANK CASING USE	D:	5 Wrought iron	8 Concre	ete tile	CASING J	OINTS: Glue	edClampe	ed
1 Steel 3 RMP	(SR)	6 Asbestos-Cement		(specify below)			ded	
2 PVC 4 ABS		7 Fiberglass					eaded	
Blank casing diameter								
Casing height above land surface	24	in., weight			lbs./ft. Wall thick	ness or guag	ge No.5	7 /
TYPE OF SCREEN OR PERFORAT			7 PV			sbestos-Cen		
	ess Steel	5 Fiberglass		P (SR)			/)	
	nized Steel	6 Concrete tile	9 AB		12 N	one used (o	pen hole)	
SCREEN OR PERFORATION OPE	NINGS ADE:	5 Gua	zed wrapped		8 Saw cut		11 None (open	hole)
			wrapped		9 Drilled hole	•	ii None (open	(Tiole)
	Mill slot Key punched	7 Toro						ft.
	• •	111	//			• -		
SCREEN-PERFORATED INTERVAL	_S: From	76 ft. to	<i>64</i>	ft., From		ft. to		tt.
CDAVEL DACK INTERVAL	From	7.0 ft. to	66	π., From	•••••	π. το)	
GRAVEL PACK INTERVA		ft. to						
	110111			11., 1 10111			,	
6 GROUT MATERIAL: 1 N	eat cement	2 Cement grout	3 Ben	tonite 4	Other			
	_	ft., From						
What is the nearest source of possib				10 Livest			Abandoned water	
•		7 Dit auton					Oil well/Gas well	Well
1 Septic tank 4 La		7 Pit privy			torage			
	ess pool	8 Sewage	•		zer storage	16 (Other (specify bel	ow)
3 Watertight sewer lines 6 Se	epage pit	9 Feedyar	rd	13 Insect	icide storage			
Direction from well?				How man	y feet?			
FROM TO	LITHOLOGIC	LOG	FROM	то	Р	LUGGING IN	NTERVALS	
0 5 13/0	ck Din	+						
C 58 01	-11	/						
J /3 /2			1 0		011	/-1/		
55, 63 Mix	fure co	arse grav	Vel, T	ne sa	nd tCI	GY		
63 66 3ha	16	7	+ • •					
		180						
			-					
					NA			
7 CONTRACTOR'S OR LANDOW	NER'S CERTIFICA	TION: This water well u	as (1) conetr	icted (2) reco	instructed or (3)	nlugged up	der my jurisdictio	on and was
completed on (mo/day/year)	72-05						nowledge and bel	
Water Well Contractor's Licence No	428				d on (pro/day/yr)		2 -05	ransas
under the business name of 577	11560	1^	vveii necoiu		1 7		e 4 01	0-
	ILUEK L	DRILLING			signature)	M	Mala	ur)
INSTRUCTIONS: Use typewriter or ball poin and Environment, Bureau of Water, Geology								

records. Fee of \$5.00 for each constructed well.