WATEI	R WEL	L RECORD	Form W	WC-5	Division of Water Resources App. No.	
	ATION (OF WATER WELL:	Fraction NW 1/4 SE 1/4	1/4 1/4	Section Number Township No. Range Number T 2 S R 22 DE VW	
Street	t/Rural A	ddress of Well Location;			Global Positioning System (GPS) information:	
from	from nearest town or intersection: If at owner's address, check				Latitude: .39-54'-20.3" (in decimal degrees) Longitude: 99-48'-12.9" (in decimal degrees)	
4 mi	les west	of Almena, 1 mile nort	h, 1/2 west, 1/4 nort	h	Elevation:	
A XX7 A 7	TITLES XX/II	I I OWNED			Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27	
RR#		ddress, Box #: P.O. Bo	Farms Inc. ox 8 land, KS 67647		Collection Method: GPS unit (Make/Model: Magellan 300 Digital Map/Photo, Topographic Map, Land Survey	
		WV119 10	ianu, NS 67047	······································	Est. Accuracy:	
	ATE WEI H AN "X"	I	COMPLETED WEL	1, 93	ft.	
	TION BO	X: Depth(s) Groun	dwater Encountered	(1).64	ft. (2) ft. (3) ft ft. below land surface measured on mo/day/yr. 03/31/12	
	N	WELL'S STAT	IC WATER LEVEL	64ft.	below land surface measured on mo/day/yr. 03/31/12	
		man varous o	test data: Well water	er waso.l	ft. after .2 hours pumping. 50 gpmft. after hours pumping gpm	
	V NI		gpm. well water	93 f	ft., andft.	
w		E Bore Hole Dian	TO BE USED AS: [☐ Public wat	ter supply Geothermal Injection well	
90	v × si		☐ Feedlot ☐	Oil field water	er supply Dewatering Other (Specify below)	
SW 2-SE						
	S	Was a chemical	l/bacteriological sampl /day/yr sample was su	e submitted to bmitted	o Department? [] Yes V No	
	1 mile		nfected? 🔽 Yes 🗌			
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: VI Glued C Clamped C Welded C Threaded						
Casing diameter 8 in to 93 ft., Diameter in to ft., Diameter in to ft.						
Casing height above land surface 24 in., Weight 3.67 lbs./ft., Wall thickness or gauge No. schd 40 TYPE OF SCREEN OR PERFORATION MATERIAL:						
Steel Stainless Steel PVC Other (Specify)						
Brass Galvanized Steel None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)						
SCREE	N-PERF	ORATED INTERVALS:	From 63	ft. to93	ft., From ft. to ft.	
			From	ft. to	ft., From ft. to ft.	
	GRAVI	EL PACK INTERVALS:	From Erom	. It. to A.A . ft. to	ft. From ft. to ft.	
From						
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other						
What is	the near	est source of possible con	tamination:			
Septic tank						
		ht sewer lines Seepage	pit Feedyard	Fertilizer s	storage Oil well/gas well none	
		n well			e from well	
FROM		LITHOLO	GIC LOG	FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
31	31 45	top soil and clay sandstone				
45	49	med. sand				
49	65	hard sandstone				
65	89	soft sandstone				
89	93	hard limestone				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged						
under my jurisdiction and was completed on (mo/day/year) .03/31/2012 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 792. This Water Well Record was completed on (mo/don/fear) 4/20/2012 under the business name of Holdrege Well Service by (signature)						
INSTRUCTIONS: Use typewriter or hall point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies						
(white, blue, pink) to Kansas Depart tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. I nelude fee of \$5.00 for each constructed well. Vi sit us at						
http://www.kdheks.gov/waterwell/index.html.						
	KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy					