


1	LOCATION OF WATER WELL: County: <u>Norton</u>	Fraction <u>SE 1/4 SE 1/4 SE 1/4</u>	Section Number <u>14</u>	Township Number <u>T 2 S</u>	Range Number <u>R 23 W</u>
---	--	---	-----------------------------	---------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?
Traction 364 283 Approx. 2 1/4 mi. N + 1 mi E

2	WATER WELL OWNER: RR#, St. Address, Box # : <u>Rt. 1 Bx 167</u> City, State, ZIP Code : <u>Norton, KS 67654</u>	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4	DEPTH OF COMPLETED WELL <u>126</u> ft. ELEVATION:
---	---	---	---

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
WELL'S STATIC WATER LEVEL 60 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No

5	TYPE OF BLANK CASING USED: 1 Steel 2 <u>PVC</u> 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped Welded Threaded
---	---	--

Blank casing diameter 5 in. to 86 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No. SOR 21

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 <u>RMP (SR)</u> 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)	SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Guazed wrapped 6 Wire wrapped 7 Torch cut 8 <u>Saw cut</u> 9 Drilled holes 11 None (open hole)
--	---

SCREEN-PERFORATED INTERVALS: From 86 ft. to 126 ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 25 ft. to 126 ft., From ft. to ft.

6	GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 <u>Bentonite</u> 4 Other
---	---

Grout Intervals: From 5 ft. to 25 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well? E How many feet? 75

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	Black dirt			
6	54	Clay			
54	70	Clay w/ traces of sand			
70	80	Fr. & med. sand			
80	123	Sandstone w/ sandy clay balls & fine through			
123	126	Ochre			

7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-16-04</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>428</u> This Water Well Record was completed on (mo/day/yr) <u>11-2-04</u> under the business name of <u>STALDER DRILLING</u> by (signature) <u>Jerry L. Stalder</u>
---	--