USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT, CLEARLY. MOERT

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)

					eka, Kansas 0002U	
County Fraction		Section number		Township number Range number		
1. Location of well: Norton	SW 1/4 SW 1/4 SW 1/4	25		, 2	_R 23 W	
	· · · · · · · · · · · · · · · · · · ·			1 3		E/W
I I MILA ABET TONTTO AT NATTAN KANESE I				ton Livestock A	uction	
Street address of well location if in city:						
				orton, Kansas 6		
4. Locate with "X" in section below:	Sketch map: 119 3A/e BA+11	 	++	6. Bore hole dia. 9 ir	Completion date	<u>17 707.7</u> 2
N 1/00/19/	''r		H	_ Well depth 70 ft.		
1			H	-7. Cable tool _XRotary		
NW NE	, / 9A/e \-	OLL	51	Hollow rod Jetted	Bored Rev	erse rotary
•	2 1 2 - 7	0/0/	1-	8. Use: Domestic F	Public supply X In	ndustry
= X-136	BATI			Irrigation A	Air conditioning S	tock
SW SE		TI	7			Other
	l	++	+	9. Casing: Material RMP		below
1 1 5/ope	-> <u> </u>	1'	<u></u>	Threaded WeldedG		in.
, , ,				RMP_X PVC Weight 80 lbs./ft. Dia 5 in. to 55ft. depth Wall Thickness: inches or		
5. Type and color of material				Diain. toft. depth Wall Thickness; inches or Diain. toft. depth gage No. 250		
5. Type and color of material		From	'°	10. Screen: Manufacturer's		
				Modern Pipe I	nc.	
Yellow clay		0	52	Type PVC	Dia5	
Sand @medium) with some wi	hite lime rocks	150	66	Slot/gauzeSlot	Length <u>15</u>	
Dana Amediana Mich Some Wi	TITLE TIME TOCKS	52	00	Set between <u>55</u>	_ft. and	ft.
Shale, blue		66	70	Gravel pack? Yes Size re	and	- 178"
		+	<u> </u>			
	16			11. Static water level:ft. below land su	urface Date 10/10	0/75
	Mar ub			12. Pumping level below lan		
	46	 	ļ	54 ft. after 13	hrs. pumping 18	a.p.m.
	20/14/1	1. 1-		ft. after		
				Estimated maximum yield	40	g.p.m.
	Alluvium			13. Water sample submitted:	mo	o./day/yr.
				Yes X No	Date	
		ļ	ļ	14. Well head completion:	-	
					12 Inches above	grade
-		 		15. Well grouted? Yes		
				With: X Neat cement Bentonite Concrete Depth: From ft. to ft.		
						+1a N
		ļ		16. Nearest source of possib ft. 170 Directionea	le contamination. Par	US
				Well disinfected upon compl		No L
				17. Pump:	Not installed	
				Manufacturer's name Aer	motor	^ " Y\
				Model number SD12-5	<u>O</u> HP <u> </u>	0112 <u>5-74</u> 1 .
				Length of drop pipe	ft. capacity 12	_g.p.m. 🔞
				Type: stypene		
		 	ļ	X Submersible	Turbir	
(Use a second s	heet if needed)			Jet Centrifugal	Recipi	rocating S
	,					 " ს
18. Elevation: 19. Remarks: Customer agrees to build concrete slab				20. Water well contractor's This well was drilled under r		I .
around well whensoil settles around pitless				is true to the best of my know		()
Topography: adpter.				John R. Fawcett & Son 167		
 				Business name Address Norton	Vances Li	cense No.
Slope Y Upland						عَا ﴿ [
Valley	* V			Signed Authorized re	presentative Dat	3/58/7/2 1V
L — Valley [:			✓ Aumorized re	h. asemanye	3ાવ્ય