

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Norton		NE 1/4 SE 1/4 NE 1/4	34	T 2 S	R 23 E (W)
Distance and direction from nearest town or city street address of well if located within city? 308 North First St in Norton Kansas					
2 WATER WELL OWNER: H.R. Kauten					
RR#, St. Address, Box # : 308 N. 1st St.					
City, State, ZIP Code : Norton Kansas 67654					
Board of Agriculture, Division of Water Resources					
Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					
4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 1110 ft.					
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.					
WELL'S STATIC WATER LEVEL 45 ft. below land surface measured on mo/day/yr 3/26/82					
Pump test data: Well water was 56 ft. after 1 hours pumping 18 gpm					
Est. Yield 18 gpm: Well water was 56 ft. after 1 hours pumping 18 gpm					
Bore Hole Diameter 7 in. to 60 ft. and in. to ft.					
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
7 Fiberglass Threaded					
Blank casing diameter 5 in. to 50 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 13 in. weight 236 lbs./ft. Wall thickness or gauge No. 2 1/4 SDR 26					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 50 ft. to 60 ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 12 ft. to 60 ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 12 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? 45 How many feet? East					
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG					
0 41 clay					
41 57 Sand Medium Coarse					
57 60 shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/31/82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 167 This Water Well Record was completed on (mo/day/yr) 4/6/82 under the business name of Fawcett Drilling by (signature) John R. Fawcett					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					