WATER WELL RECORD	Form WWC-5	Div	ision of V	Vater Res	ources App	. No. 🕳	011025	روز
1 LOCATION OF WATER WELL:		1.5	Section N	lumber	Townshi	p Number	Range N	lumber
Decatur Street/Rural Address of Well Location; if unk	nown, distance & direction	SE ¼	lobal Pos	sitioning	System (2 s GPS) inform	ation:	LE MM
from nearest town or intersection: If at owner' From Oberlin—5 miles west—3 north	s address, check here \square .		Latitude:	e:			(in decima	l degrees)
2 WATER WELL OWNER Jeff Tor			Datum:	WGS 8	4, □ NAI	D 83, □ N	AD 27	
RR#, St. Address, Box # Box 567 City, State, ZIP Code Hoxie, KS 67740		9	Collection Method: ☐ GPS unit (Make/Model:					
City, State, ZIF Code Hoxie,	KS 07/40					graphic Map,	☐ Land Sur	vey
			Est. Accura	ıcy: □ <3	m, 🗆 3-5 m	n, 🗖 5-15 m,	□ >15 m	
3 LOCATE WELL	COLUMN TOWNS 11151 1		200		C.			
WITH AN "X" IN 4 DEPTH OF Depth(s) Ground	COMPLETED WELL water Encountered (1)		200 ft	(2)	^{It.}	ft (3)		ft
N WELL'S STATI	C WATER LEVEL N	A ft.	below lar	· (<i>2)</i> id surface	measured	on mo/day/y	 т	
	np test data: Well water v							
	gpm: Well water v							
WELL WATER TO BE USED AS: Public was				☐ Geothe	rmal	☐ Inject	ion well	
Dewatering Domestic Feedlot Moil field water supply Dewatering Dether (Specify bel						elow)		
	Industrial Domestic-la							
	bacteriological sample subm day/yr sample was submitted							
1 mile Water Well Disi	nfected? \(\bar{\bar{\bar{\bar{\bar{\bar{\bar{	o O						
5 TYPE OF CASING USED: Steel								
CASING JOINTS: X Glued Clams	oed □Welded Ū	Threade	ed					
Casing diameter 4.5 in. to 16 Casing height above land surface	ft., Diameter	in.	. to	ft.,	Diameter		in. to	ft.
TYPE OF SCREEN OR PERFORATION MA	18 in., Weight	2.38	II	bs./ft. Wa	all thickness	s or gauge N	io <u>.</u>	248
☐ Steel ☐ Stainless Steel	▼ PVC		(Specify)					
☐ Brass ☐ Galvanized Steel	None used (open hol	e)						
SCREEN OR PERFORATION OPENINGS A ☐ Continuous Slot ☐ Mill slot	ARE:	Torch cu	t 🗆	Drilled	holes [None (ope	n hole)	
☐ Louvered shutter ☐ Key punched	☐ Gauze wrapped ☐ Wire wrapped ☐	Saw cut		Other (s	pecify)			
SCREEN-PERFORATED INTERVALS:	From 160	ft. to	200	ft Fr	om	ft. t	0	ft.
GRAVEL PACK INTERVALS:	From 20	ft. to	200	ft Fr	om	ft. t	o 	ft.
	From	ft. to		ft., Fr	om	ft. t	0	ft.
6 GROUT MATERIAL: ☐ Neat cemer	nt Cement grout	⊠ Bent	onite	Other				
Grout Intervals From 0 ft. to	20 ft. From	ft.	to	ft.	From		_ ft. to	ft.
What is the nearest source of possible contam		l Livestocl	k pens	☐ Insect	ticide storas	ge 🗆 O	ther (speci	fy below)
☐ Sewer lines ☐ Cesspool	☐ Sewage lagoon ☐	Fuel stor	age		doned wate	r well		•
☐ Watertight sewer lines ☐ Seepage p	oit	Fertilizer Distance f	_		ell/gas well	Non	<u>e</u>	
	LOGIC LOG	FROM	TO) LOG (cos	nt.) <u>or</u> PLUC	GING IN	TERVALS
0 2 Surface	LOGIC LOG	160	182		v/caliche l		JOHN JIN	LKVILO
2 17 Loess		182	188	Fine to	some me			
17 63 Clay w/caliche str		188	220	Yellov	v ochre			
63 73 Fine & med sand v 73 94 Caliche & clay w/s	w/clay & caliche strks sand lenses							
94 98 Caliche w/sand str								
	sand w/caliche strks							
121 140 Clay & caliche w/s 140 160 Fine sand & sandy	sand strks y clay mix w/clay &			-				
Caliche strks	ciuj ilita w/ciuj ce							
7 CONTRACTOR'S OR LANDOWN		N: This w	vater well	was con	structed, re	constructed,	or 🗆 plug	ged
under my jurisdiction and was completed on (Kansas Water Well Contractor's License No.		Jater Well	and thi	s record i	s true to the	best of my	knowledge	e and belief -/l
under the business name of Woofter Pum	p & Well Inc.	by (signati	ure)		(1/50)	Here		- <i>1</i> 8
INSTRUCTIONS: Please fill in blanks and check the	e correct answers. Send three cor	nies (white. I	blue. p ink)	ta Kansas	Department	of Health and	Environme	nt, Bureau o
Water, Geology Section, 1000 SW Jackson St., Sui one for your records. Include fee of \$5.00 for each	ite 420, Topeka, Kansas 66612-	-1367. Tele	phone 785	-296-5522	. Send one to	o WATER W	ELL OWNE	ER and retain

Check: ☐ White Copy, ☐ Blue Copy, ☐ Pink Copy