1 LOCATION OF WATER WELL: Fraction Section Number Township No. Range Number County: REPUBLIC 4 NE 4 NW 4 NW 4 D T 2 S R 3 E	
County: REPUBLIC W NE W NW W NW W 2 T 2 S R 3 TE	
	<u> </u>
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:	
from nearest town or intersection: If at owner's address, check here	
COUNTY ROADS G AND 17 Longitude: 097.6283889 (in decimal deg	ees)
Datum: WGS 84, V NAD 83, NAD 27	
2 WATER WELL OWNER: ALAN HURLEY Collection Method:	
RR#, Street Address, Box #: 2055 REPUBLIC LANE	
City, State, ZIP Code : REPUBLIC, KS 66964 Digital Map/Photo, Topographic Map, Land Su	vey
Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 60 ft.	
SECTION BOX: Depth(s) Groundwater Encountered (1)	. ft.
N WELL'S STATIC WATER LEVEL. 30 ft. below land surface measured on mo/day/yr	
Pump test data: Well water was. 2ft. after. 4 hours pumping. 20	pm
EST. YIELDgpm. Well water wasft. after hours pumping	pm
W E Bore Hole Diameter 48in. toft., andin. toft.	
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well	
Domestic Feedlot Oil field water supply Dewatering Other (Specify bel	w)
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well LIVESTOCK Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No	
S If yes, mo/day/yr sample was submitted	
was submitted: Water well disinfected? Yes No	
5 TYPE OF CASING USED: Steel PVC Other	
CASING JOINTS: Glued Clamped Welded Threaded	
Casing diameter .16 in. to .20 ft., Diameter in. to ft., Diameter in. to	Đ.
Casing height above land surface. 18 in., Weight 15.853 lbs./ft., Wall thickness or gauge No500	. 11.
TYPE OF SCREEN OR PERFORATION MATERIAL:	
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)	
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)	
SCREEN-PERFORATED INTERVALS: From	ft
From ft. to ft., From ft. to	ft.
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to	ft.
From ft. to ft., From ft. to	ft.
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ✓ Bentonite ☐ Other	
Grout Intervals: From .3	ft.
What is the nearest source of possible contamination:	
□ Septic tank □ Lateral lines □ Pit privy □ Livestock pens □ Insecticide storage □ Other (specify below) □ Sewer lines □ Cesspool □ Sewage lagoon □ Fuel storage □ Abandoned water well	
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oii well/gas well	
Direction from well	
FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERV	ALS
0 6 TOP SOIL	
6 23 TAN CLAY	
23 34 TAN CLAY - LAYERS OF LIMESTONE	
34 42 TAN CLAY	
42 45 TAN SANDY CLAY	
45 56 SANDY GRAVEL	
56 58 YELLOW AND TAN CLAY	
58 60 SHALE	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugg	
under my jurisdiction and was completed on (mo/day/year) 9-26-2013 and this record is true to the best of my knowledge and bel	of Di
Kansas Water Well Contractor's License No. 480 This Water Well Record was completed on (mg/day/year). 9/8/2014	51.
under the business name of WILLIAMS DRILLING CO. INC by (signature)	
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check and correct answers. Sent the correct answers.	y to
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send of a co	y to