


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 SE 1/4 Section Number 33 Township Number T 2 S Range Number R 38 E/W
 County: CHEYENNE

Distance and direction from nearest town or city street address of well if located within city?
1 N - 3 W OF BIRD CITY

2 WATER WELL OWNER: SAM BEESON
 RR#, St. Address, Box # : HC 2 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : BIRD CITY, KS 67731 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL 276 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 172 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 172 ft. below land surface measured on mo/day/yr 5-25-06
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 15 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 236 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. SDR 26
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 236 ft. to 276 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 0 ft. to 276 ft., From ft. to ft.

6 GROUT MATERIAL: Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? None in View How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	40	SAND-CLAY			
40	80	CLAY			
80	100	STONE-CLAY			
100	120	STONE-GRAVEL-SAND			
120	140	GRAVEL-SAND-CLAY			
140	160	SAND-CLAY			
160	180	CLAY			
180	220	SAND-CLAY			
220	240	STONE-CLAY			
240	260	CLAY			
260	276	SHALE-SAND-CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (constructed) (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-25-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 484 This Water Well Record was completed on (mo/day/yr) 6-20-06 under the business name of SCHAAL DRILLING Co by (signature) [Signature]