WATE:	R WEL	L RECORD	Form W	WC-5	Division of Wa	ter Resources App. N	o. L	
1 LOCATION OF WATER WELL: County: Republic			Fraction 1/4 SE 1/4 SW	1/4 SE 1/4	Section Number 19		Range Number R 4 □E ☑W	
Stree	Street/Rural Address of Well Location; if unknown, distance & direction					Global Positioning System (GPS) information:		
from	from nearest town or intersection: If at owner's address, check here \square .					Latitude: .39.8575. (in decimal degrees) Longitude: 97.807444 (in decimal degrees)		
	Go South out of Republic on Road 70 to Lincoln Road and west for 3/4 of a mile					Elevation:		
2 WATER WELL OWNER: Richard Sandell					Collection Method:			
RR#, Street Address, Box #: P O Box 28					☐ GPS unit (Make/Model: Garmin) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
	, State, Z	T CEPUDIN	c, KS 66964		☐ Digital Map/l Est. Accuracy: ☐	Photo, ☐ Topographi <3 m, ☐ 3-5 m, ☐	ic Map,	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 37								
	TION BO	OX: Depth(s) Groundwater Encountered $(1).23$ ft. (2) ft. (3) ft.						
	N	WELL'S STATIC WATER LEVEL. 23ft. below land surface measured on mo/day/yr						
	Pump test data: Well water wasft. after hours pumping							
EST. YIELD. 5gpm. Well water wasft. after								
W	W Bore Hole Diameter 12in. to .37ft., andin. toft. WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
□ Domestic □ Feedlet □ Oil field water supply □ Description □ Other (Specify below)							Other (Specify below)	
☐ Irrigation ☐ Industrial ☐ Domestic lawn & garden ☐ Monitoring well								
Was a chemical/bacteriological sample submitted to Department? Yes No								
S If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected?								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .5								
Casing height above land surface. 18 in., Weight 2.893 lbs./ft., Wall thickness or gauge No265								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From								
From								
Grout Intervals: From .3								
What is the nearest source of possible contamination:								
Septic tank								
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Direction from well								
FROM	TO	LITHOLOG		FROM			JGGING INTERVALS	
0	3	Top Soil	200	1110111	Lilio.	200 (cont.) or 1 De	JOHN HILKYALD	
3	13	Tan Clay	100.00					
13	17	Fine to Medium Sand						
17	26	Fine to Medium Sand a						
26	37	Fine to Medium with so	me Coarse					
		White Gravel						
37		Shale						
				-				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .09/23/2009 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 480 This Water Well Record was completed on (mo/day/year) 10/08/2009								
under the business name of Williams Drilling Co., Inc. by (signature) by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: ✓ White Copy, ☐ Blue Copy, ☐ Pink Copy								