


1 LOCATION OF WATER WELL: County: SUMNER Fraction: NW 1/4 NE 1/4 NE 1/4 Section Number: 1 Township Number: T 30 S Range Number: R 1 EW

Distance and direction from nearest town or city street address of well if located within city?
936 B ST. PECK, KS 67120

2 WATER WELL OWNER: FRA DIETRICH
 RR#, St. Address, Box #: 12089 CROW LANE Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: PECK, KS 67120 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 16 ft. 2. 16 ft. 3. 16 ft.
 WELL'S STATIC WATER LEVEL: 16 ft. below land surface measured on mo/day/yr 4-8-88
 Pump test data: Well water was 16 ft. after 2 hours pumping 25 gpm
 Est. Yield 40 gpm Well water was 16 ft. after 2 hours pumping 25 gpm
 Bore Hole Diameter: 11 in. to 40 ft., and 11 in. to 40 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass 10 Asbestos-cement Threaded
 Blank casing diameter 5 in. to 20 ft., Dia. 5 in. to 20 ft., Dia. 5 in. to 20 ft., Dia. 5 in. to 20 ft.
 Casing height above land surface 24 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 250
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 20 ft. to 40 ft., From 20 ft. to 40 ft., From 20 ft. to 40 ft., From 20 ft. to 40 ft.
 GRAVEL PACK INTERVALS: From 16 ft. to 40 ft., From 16 ft. to 40 ft., From 16 ft. to 40 ft., From 16 ft. to 40 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 0-3' SURFACE SOIL
 Grout intervals: From 3 ft. to 16 ft., From 3 ft. to 16 ft., From 3 ft. to 16 ft., From 3 ft. to 16 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? SOUTH How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	FILL DIRT			
3	7	SURFACE SOIL			
7	15	CLAY STRIPES OF SAND			
15	20	FINE SAND			
20	32	COURSE SAND			
32	40	COURSE SAND SMALL GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-8-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 4-15-88 under the business name of PAUL H. METZGER WELL DIGGER DRILLING (Signature) Paul H. Metzger
 INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4