

1) LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SUMNER		N 1/4 S 1/4 NE 1/4	2	T 30 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city: 1 MILE WEST 1/4 MILE SOUTH OF PECK KANSAS					
2) WATER WELL OWNER: MELVIN WOHLFORD		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: P.O. BOX 142A		Application Number:			
City, State, ZIP Code: PECK, KANSAS 67120					
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4) DEPTH OF COMPLETED WELL: 29 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 17 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 4-4-88 Pump test data: Well water was 10 ft. after 2 hours pumping 30 gpm Est. Yield 50 gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to 29 ft., and .in. to .ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well (1) Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No..... If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes [X] No			
5) TYPE OF BLANK CASING USED:		CASING JOINTS: Glued [X] Clamped			
1 Steel 3 RMP (SR) (2) PVC 4 ABS Blank casing diameter 5 in. to 24 ft., Dia. in. to .ft., Dia. in. to .ft. Casing height above land surface 30 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 250		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass Welded Threaded			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped (8) Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)		SCREEN-PERFORATED INTERVALS: From 24 ft. to 29 ft.			
GRAVEL PACK INTERVALS: From 17 ft. to 29 ft.					
6) GROUT MATERIAL: (1) Neat cement 2 Cement grout 3 Bentonite 4 Other 0-3' SURFACE SOIL		Grout Intervals: From 3 ft. to 17 ft.			
What is the nearest source of possible contamination:		1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage			
Direction from well? WEST		How many feet? 125			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0 3 SURFACE SOIL					
3 17 CLAY					
17 20 FINE SAND					
20 28 COURSE SAND					
28 29 SHALE					
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-4-88 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 4-15-88					
under the business name of RALPH METZGER WELL DIGGING DRILLING & RESTORATION					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					