


1 LOCATION OF WATER WELL		Section <u>SE 1/4 SE 1/4</u>		Section Number <u>9</u>		Township Number <u>T 30 S</u>		Range Number <u>R 10 E/W</u>	
County: <u>Rayman</u>		Distance and direction from nearest town or city? <u>4 East on 42 Hwy North Side of Hwy</u>		Street address of well if located within city?					
2 WATER WELL OWNER: <u>BRUCE HART</u>		RR#, St. Address, Box #: <u>NASHVILLE, Kansas</u>		Board of Agriculture, Division of Water Resources Application Number: <u>SEP 10 3 80 28588 *****1.00</u>					
City, State, ZIP Code <u>67112</u>									
3 DEPTH OF COMPLETED WELL <u>60</u> ft.		Bore Hole Diameter <u>8"</u> in.		to <u>60</u> ft.		and <u>60</u> in. to <u>60</u> ft.			
Well Water to be used as:		5 Public water supply		8 Air conditioning		11 Injection well			
1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering			
2 Irrigation		4 Industrial		7 Lawn and garden only		10 Observation well			
Well's static water level <u>40</u> ft.		below land surface measured on <u>8-16</u> month		<u>16</u> day		<u>1980</u> year			
Pump Test Data <u>NA</u>		Well water was <u>NA</u> ft. after		hours pumping		gpm			
Est. Yield <u>NA</u> gpm		Well water was <u>NA</u> ft. after		hours pumping		gpm			
4 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile		Casing Joints: Glued <input checked="" type="checkbox"/> Clamped <input type="checkbox"/>			
1 Steel		3 RMP (SR)		6 Asbestos-Cement		Welded <input type="checkbox"/>			
<u>0</u> PVC		4 ABS		7 Fiberglass		Threaded <input type="checkbox"/>			
Blank casing dia <u>5</u> in.		to <u>5</u> ft.		Dia <u>5</u> in.		to <u>5</u> ft.			
Casing height above land surface <u>2 feet</u>		in., weight <u>34</u> lbs./ft.		Wall thickness or gauge No <u>34</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		<u>0</u> PVC		10 Asbestos-cement					
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)			
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS			
Screen or Perforation Openings Are:		5 Gauzed wrapped		<u>0</u> Saw cut		11 None (open hole)			
1 Continuous slot		3 Mill slot		6 Wire wrapped		9 Drilled holes			
2 Louvered shutter		4 Key punched		7 Torch cut		10 Other (specify)			
Screen-Perforation Dia <u>5"</u>		in. to <u>5"</u>		ft. Dia <u>5"</u>		in. to <u>5"</u>			
Screen-Perforated Intervals:		From <u>40</u> ft.		to <u>60</u> ft.		From <u>40</u> ft.		to <u>60</u> ft.	
Gravel Pack Intervals:		From <u>10</u> ft.		to <u>60</u> ft.		From <u>10</u> ft.		to <u>60</u> ft.	
5 GROUT MATERIAL:		1 Neat cement		2 Cement grout		3 Bentonite		4 Other	
Grouted Intervals: From <u>10</u> ft.		to <u>10</u> ft.		From <u>10</u> ft.		to <u>10</u> ft.		From <u>10</u> ft.	
What is the nearest source of possible contamination:		1 Septic tank		4 Cess pool		7 Sewage lagoon		10 Fuel storage	
<u>0</u> Sewer lines		5 Seepage pit		8 Feed yard		11 Fertilizer storage		14 Abandoned water well	
3 Lateral lines		6 Pit privy		9 Livestock pens		12 Insecticide storage		15 Oil well/Gas well	
Direction from well <u>West</u>		How many feet <u>50</u>		Water Well Disinfected? <u>Yes</u>		No			
Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u>		If yes, date sample was submitted <u>month</u> day year		Pump Installed? <u>Yes</u>		No			
If Yes: Pump Manufacturer's name <u>STAY RITE</u>		Model No. <u>811</u>		HP <u>12 HP</u>		Volts <u>230</u>			
Depth of Pump Intake <u>50 Feet</u>		ft.		Pumps Capacity rated at <u>18 GPM</u>		gal./min.			
Type of pump:		<u>0</u> Submersible		2 Turbine		3 Jet		4 Centrifugal	
		5 Reciprocating		6 Other					
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>0</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on <u>8</u> month <u>13</u> day <u>1980</u> year									
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>226</u>									
This Water Well Record was completed on <u>8 13 80</u> month <u>13</u> day <u>1980</u> year under the business name of <u>Leon G. Webb</u> by (signature)									
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		FROM		TO		LITHOLOGIC LOG		FROM	
		TO <u>SE 1/4</u>		TO <u>1</u>		Brown Sand		FROM	
		<u>10</u>		<u>10</u>		White H.P.		TO	
		<u>20</u>		<u>20</u>		Sand fine			
		<u>30</u>		<u>30</u>		Coarse Gravel			
		<u>40</u>		<u>40</u>		Coarse Gravel			
		<u>50</u>		<u>50</u>		Coarse Gravel			
		<u>60</u>		<u>60</u>		Coarse Gravel			
ELEVATION:		TOTAL		Depth of Well		<u>60 feet</u>			
				Clay Bottom					
Depth(s) Groundwater Encountered		1. <u>1</u> ft.		2. <u>1</u> ft.		3. <u>1</u> ft.		4. <u>1</u> ft.	
(Use a second sheet if needed)									

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top two copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER retain one for your records.