

1 LOCATION OF WATER WELL:	Fraction $\frac{1}{4}$ SW $\frac{1}{4}$	Section Number 19	Township Number T 30 S	Range Number R 10 E/W
---------------------------	---	-------------------	------------------------	-----------------------

County: Kingman

Distance and direction from nearest town or city street address of well if located within city?

City of Nashville Kansas2 WATER WELL OWNER: HAROLD HUSSRR#, St. Address, Box # : Box 23

Board of Agriculture, Division of Water Resources

City, State, ZIP Code

67112

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr 9-22-92

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 12 in. to 60 ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was sub-mitted Water Well Disinfected? Yes ☒ No

5 TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued Clamped

6 Asbestos-Cement

9 Other (specify below)

Welded

7 Fiberglass

Threaded

4 ABS

Blank casing diameter 5 in. to 40 ft., Dia in. to ft., Dia in. to ft.Casing height above land surface 2 feet in., weight lbs./ft. Wall thickness or gauge No. 14

TYPE OF SCREEN OR PERFORATION MATERIAL:

5 Fiberglass

① PVC

10 Asbestos-cement

6 Concrete tile

9 ABS

11 Other (specify)

4 Galvanized steel

12 None used (open hole)

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE:

From 40 ft. to 60 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 10 ft. to 50 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:

① Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From 1 ft. to 10 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

7 Pit privy

10 Livestock pens

14 Abandoned water well

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well? WestHow many feet? 180 ft

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top Soil			
1	10	Clay			
10	20	Soft grey clay			
20	30	Soft grey clay			
30	40	Clay			
40	50	Soft coarse			
50	60	TOTAL DEPT			
		60 feet clay			
		Bottom			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was

completed on (mo/day/year) 9-22-92 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. 226 This Water Well Record was completed on (mo/day/yr) 9-22-92under the business name of Weber Well Service by (signature) Ken A. Weber