

1 LOCATION OF WATER WELL: County: Kingman	Fraction NW 1/4 N W 1/4 NE 1/4	Section Number 16	Township Number T 30 S	Range Number R 10 E/W
---	---------------------------------------	--------------------------	-------------------------------	------------------------------

Distance and direction from nearest town or city street address of well if located within city?

in Nashville block 14 lots 8 & 9

2 WATER WELL OWNER: Mrs Fred Westerman RR#, St. Address, Box #: Nashville, Ks. 67112 City, State, ZIP Code:	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 62 ft. ELEVATION:
--	--

	Depth(s) Groundwater Encountered 1. 44 ft. 2. 44 ft. 3. 44 ft. WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 8-23-91 Pump test data: Well water was 20 gpm. Well water was 62 ft. after 8-23-91 hours pumping 20 gpm. Est. Yield 20 gpm. Well water was 62 ft. after 8-23-91 hours pumping 20 gpm. Bore Hole Diameter 9 in. to 62 ft., and 62 in. to 62 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No . If yes, mo/day/yr sample was submitted No . Water Well Disinfected? Yes No
--	---

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 5 in. to 52 ft., Dia 52 in. to 52 ft., Dia 52 in. to 52 ft.			11 Other (specify)
Casing height above land surface 20 in., weight 20 lbs./ft. Wall thickness or gauge No. 210			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	11 Other (specify)
1 Steel	3 Stainless steel	9 ABS	12 None used (open hole)
2 Brass	4 Galvanized steel	6 Concrete tile	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	9 Drilled holes	
2 Louvered shutter	4 Key punched	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:	From 52 ft. to 62 ft.		
GRAVEL PACK INTERVALS:	From 23 ft. to 62 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 3 ft. to 23 ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? N			How many feet? 50	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	soil			
2	17	clay			
17	28	fine sand			
28	44	clay			
44	61	med. sand			
62	62	clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-23-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 140 This Water Well Record was completed on (mo/day/yr) 9-6-91 under the business name of Lyman Inc. by (signature) <i>Lyman Inc.</i>
